

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T30-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7378)

-----  
Marked a Fir 20" dia., for cor. secs. 18, 19, 13 and 24, from which

- A Fir 24" dia., bears N.10°W., 86 lks. dist.
- A Fir 20" dia., bears S.80°W., 5 lks. dist.
- A Laurel 6" dia., bears S.60°E., 27 lks. dist.
- A Laurel 5" dia., bears N.70°E., 23 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7407)

-----  
To summit of rocky bluff and Set a stone, 16x12x8 ins., 12" in the ground for cor. to secs. 13, 18, 19 and 24, mkd. with 3 notches on N. and S. edges, from which

- A Fir 40" dia., bears S.85½°W., 211 lks. dist. mkd. T30S R10W S24 BT.

Raised a mound of stone, 4 ft. base, 3 ft. high alongside of cor.

Corner is on the blazed line.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 1965 - C.S. File 53/53-33

-----  
Found - No trace of mound of rock or stone.

- 40" D.Fir now 52", S.85½°W., 139.3 ft. Tree had been opened and badly burned. Re-opened stump for scribing "S".

Set Brass cap at cor. mkd: County Surveyors Office

	T 30	S	
R10W	S 13	S 18	R9W
	S 24	S 19	
	1965		

- New BTs- 17" D.Fir N.47°E., 14.0 ft. "T30S R9W S18 CS BT."
- 19" D.Fir N.38°W., 16.3 ft. "T30S R10W S13 CS BT"
- 19" Cedar S.48°W., 7.0 ft. "T30S R10W S24 CS BT"
- 6" Hemlock S.7°E., 13.0 ft. "R9W S19 CS BT"

Corner is about 20.0 ft. North of rock bluff.

Fd. OK, Feb. 1974 by B. Shaner - M 49-54

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T30-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM survey by Joel E. Robb, Cadastral Surveyor, under Group #1269, Surveyed May/Aug. 1985 - (DCSO records Vol. 49 Page(s) 18747-48)

-----

The Sec. Cor., perpetuated and recorded by Powell in 1965, monumented with an iron post 1¼" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1965, from which the remains of the original bearing tree

A sawed Fir stump 68" dia., bears S.85½°W., 211 lks. dist., with illegible scribe marks visible on opened blaze.

and bearing trees mkd. by Powell

A Fir 22" dia., bears N.47°E., 21 lks. dist., with healed blaze.

A Hemlock 10" dia., bears S.7°E., 19½ lks. dist. with healed blaze.

A Cedar 23" dia., bears S.54°W., 10½ lks. dist. with healed blaze.

A Fir 30" dia., bears N.36½°W., 25 lks. dist. with healed blaze.

and a new bearing object

An X BO on a rock cliff, 20 ft. high, bears S.32½°W., 38 lks. dist.