

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T30-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7378)

Set ¼ sec. post, from which
A Cedar 5" dia., bears N.12°E., 7 lks. dist.
A Willow 4" dia., bears N.42°W., 13 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7410)

Set stone 14x14x10 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 12" dia., bears N.45 3/4°E., 70 lks. dist. mkd. ¼ S BT.
A Fir 13" dia., bears N.26½°W., 52¼ lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 1965 - C.S. File 53/53-30

Found - Stone at ¼ cor., 14x14x10" mkd. ¼ on W. face.
13" D.Fir now 20", N.26½°W., 34.3 ft., opened & found scribe "¼S".
12" D.Fir N.45 3/4°E., 46.2 ft. No trace of this tree because of skid road.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S
¼ R10W S13 | S19 R9W
1965
New BTs- 19" D.Fir N.5°W., 42.4 ft. scribed ¼ S13 CS BT.
7" D.Fir N.87°E., 8.0 ft. scribed ¼ S18 CS BT.

Fd. OK, Feb. 1974 by B. Shaner - M 49-54

BLM Resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1269, Surveyed May/Aug. 1985 - (DCSO records Vol. 49 Page(s) 18744-45)

The ¼ sec. cor., perpetuated and recorded by Powell in 1965, and recorded by Shaner in 1974, monumented with an iron post 1" dia., firmly set, projecting 6" above ground, alongside of which is the original sandstone 14 x 14 x 10 ins., with ¼ visible on W. face, and with brass cap mkd. in 1965, from which the remains of the original bearing trees:
(Cont. Next Page)

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 18; & 13, T30-10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

A sawed Fir stump 25" dia., bears N.26½°W., 52¼ lks. dist., with fragmentary scribe marks visible on opened blaze.
and the remains of the bearing trees mkd. by Powell:
A Fir 12" dia., bears S.84°E., 12½ lks. dist., with healed blaze.
A Fir stub, size indeterminate, bears N.5°W., 64 lks. dist., no marks remaining.
and a new bearing tree:
A Fir 15" dia., bears S.15°W., 130 lks. dist., mkd. ¼ S13 BT.
Deposit original stone alongside the iron post.