

PRIMARY CORNER DESCRIPTION Sec Cor for 7 & 18; 12 & 13, T30-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7377-78)

-----  
 Set post cor. secs. 7, 18, 12 and 13, from which  
 A Cedar 30" dia., bears N.5°W., 80 lks. dist.  
 A Myrtle 15" dia., bears S.25°E., 13 lks. dist.  
 A Myrtle 20" dia., bears N.80°E., 15 lks. dist.  
 A Myrtle 15" dia., bears S.10°W., 54 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7409)

-----  
 Set a stone 14x12x10 ins., 10" in the ground for cor. to secs. 7, 12, 13 and 18, marked with 2 notches on N. and 4 notches on S. edges, from which  
 A Cedar 36" dia., bears N.46°E., 41½ lks. dist., mkd. T30S R9W S7 BT.  
 A Myrtle 10" dia., bears S.52½°E., 65½ lks. dist. mkd. T30S R9W S18 BT.  
 A Cedar 30" dia., bears S.63½°W., 42½ lks. dist. mkd. T30S R10W S13 BT.  
 A Cedar 26" dia., bears N.56½°W., 37 lks. dist. mkd. T30S R10W S12 BT.  
 This cor. is on E. bank of creek, 7 lks. wide, course S.5°W.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1964 - C.S. File 53/53-73

-----  
 Found - Rock 12x10x10" with 4 notches on S. edge. N. edge broken off.  
 36" Cedar stump N.46°E., 27.4 ft., shows orig. "R BT" scribe and new scribe "S7 183 BT". (1893)  
 30" Cedar stump S.63½°W., 28.1 ft. Do not open.  
 26" Cedar, face down & rotten, N.56½°W., 24.4 ft.

Set Brass cap at cor. mkd. Doug County Surveyors Office (In mound of stone)

	T 30 S		
R10W	S 12	S 7	R9W
	S 13	S 18	
	1964		

New BTs- 7" Myrtle N.65°E., 7.0 ft. mkd. S7 DCS BT.  
 16" Alder S.4°E., 38.6 ft. mkd. T30S R9W S18 DCS BT  
 6" Maple S.16°W., 22.3 ft. mkd. T30S R10W S13 DCS BT  
 15" Alder N.33°W., 36.8 ft. mkd. T30S R10W S12 DCS BT.

Corner lies on E. bank of creek approx. 3.0 ft. above creek.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T30-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1269, Surveyed May/Aug. 1985 - (DCSO records Vol. 49 Page(s) 18746-47)

-----

The Sec. Cor., perpetuated and recorded by Gearhart, Coos County Surveyor in 1951, further perpetuated and recorded by Tracy in 1964, monumented with an iron post 1¼" dia., loosely set in a mound of stone, 1 ft. base, with brass cap mkd. by DCSO in 1964, from which the remains of the original bearing trees:

A sawed Cedar stump 35" dia., bears N.46°E., 35 lks. dist. with scribe marks S7 183 BT visible on open blaze. (Rec. 41½ lks.)

A decayed Cedar stump 30" dia., bears S.63½°W., 42½ lks. dist., no marks visible.

A sawed Cedar stump 42" dia., bears N.64°W., 50 lks. dist., with healed blaze. (Rec. N.56½°W., 37 lks.)

and the remains of a bearing tree mkd. by Gearhart:

A sawed Cedar stump 25" dia., bears West 30 lks. dist. with scribe marks S12 183 BT visible on open blaze.

and bearing trees mkd. by Tracy:

A Myrtle 10" dia., bears N.65°E., 10½ lks. dist., with illegible scribe marks visible on partially healed blaze.

An Alder 20" dia., bears S.4°E., 58 lks. dist., with healed blaze.

An Alder 20" dia., bears N.33°W., 55 lks. dist., with healed blaze.

At the corner point

Set a brass tablet, ¾" dia., ¾" stem, in an iron pipe, 1" dia., 12" long, in a drill hole, 8" deep, in solid bedrock, with top mkd.

T 30 S			
R 10 W		R 9 W	
S 12		S 7	
S 13		S 18	
1985			

from which new bearing trees:

A Fir 17" dia., bears N.8°E., 72 lks. dist. mkd. T30S R9W S7 BT.

A Fir 17" dia., bears S.71°W., 45 lks. dist. mkd. T30S R10 S13 BT.

A Fir 10" dia., bears N.75°W., 47½ lks. dist., mkd. T30S R10W S12 BT.

Deposit iron post at base of iron pipe.

Fd. BC & 8 BTs by T. Hostetter, 3/2008 - M155-26

continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 7 & 18; 12 & 13, T30-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM retracement by Aaron M Graham, Cadastral Surveyor, under Group No 2164, surveyed June/Oct. 2007 - (DCSO records Vol. 56 Page(s) 22256-8 and BLM Plat 2010-1 & 2010-2)

-----  
 The cor. of secs. 7, 12, 13, & 18, on the W bdy. of the Tp., rehabilitated by JN Gearhart, Coos Co. Surveyor, in 1951, filed in the Coos County Surveyor's Office, under Map No 4085 and in Book 7, page 94 perpetuated by Vernon R. Tracy, Dep. (Douglas) Co. Surveyor, in 1964, and remonumented by Robb in 1985, determined at distance-distance intersection from the BTs mkd. by Robb; from which the remains of the orig. BTs.

A cedar stump, 34" dia., bears N.42½°E., 23.1 ft., with scribe marks S7 183 BT visible on open blaze. (Record, N.46°E.)

A cedar stump, 24" dia., bears S.66°W., 26.3 ft., no marks visible. (Record, S.63½°W., 28,1 ft.)

A cedar stump, 44" dia., bears N.62½°W.. 33.0 ft., with a healed blaze. (Record, N.64°W.)

and the remains of a BT mkd. by Gearhart, & reported by Robb

A cedar stump, 25" dia., bears W., 19.8 ft., with scribe marks S12 183 BT visible on partially healed blaze.

and the BTs mkd. by Tracy, reported by Robb

An alder, 22" dia., bears S.5½°E., 38.9 ft., with a healed blaze. (Record, S.4°E., 38.3 ft.)

An older, 19" dia., bears N.36°W., 36.9 ft., with a healed blaze. (Record, N.33°W., 36.3 ft.)

and the bearing trees mkd. by Robb

A fir, 28" dia., bears N.5½°E., 47.5 ft., with a healed blaze. (Record, N.8°E.)

A fir, 23" dia., bears S.74½°W., 29.7 ft., with a healed blaze. (Record, S.71°W.)

At the corner point

Drive an iron rod, 18" long, ¾" dia., 18' into sandstone bedrock, with aluminum cap mkd:

T30S	
R10W	R9W
S 12	S 7
S 13	S 18
2007	