

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T30-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7377)

-----  
Set post cor. of secs. 6, 7, 1 and 12, from which  
A Fir 15" dia., bears N.72°E., 407 lks. dist.  
A Fir 15" dia., bears S.2°W., 438 lks. dist.  
A Fir 15" dia., bears S.2°E., 420 lks. dist.  
A rock 1½ ft. high, 2 ft. in dia., (marked (+), bears N.45°W., 32 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #6130, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7408)

-----  
Set a stone 14x12x10 ins., 10" in the ground for cor. to secs. 1, 6, 7 and 12, marked with 1 notch on N. and 5 notches on S. edges, from which  
A Fir 14" dia., bears N.7°E., 42 lks. dist. mkd. T30S R9W S6 BT.  
A Fir 16" dia., bears S.79°E., 29½ lks. dist. mkd. T30S R9W S7 BT.  
A Fir 10" dia., bears S.39½°W., 49 lks. dist. mkd. T30S R10W S12 BT.  
A Fir 12" dia., bears N.60°W., 34 lks. dist. mkd. T30S R10W S1 BT.  
I am unable to find either the old sec. cor. or the witness trees.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #477, surveyed July 1962 - (DCSO records Vol. 31 Page(s) 13177)

-----  
The Sec. cor. re-established by Bushey in 1893, determined at record bearing and distance from the 1893 BTs:  
A Fir 28" dia., bears N.7°E., 42 lks. dist., with scribe marks O W visible on partly opened blaze.  
A Fir 36" dia., bears S.79°E., 29½ lks. dist., with healed blaze.  
A Fir 24" dia., bears S.39½°W., 49 lks. dist., with healed blaze.  
A Fir 28" dia., bears N.60°W., 34 lks. dist., with healed blaze.

At the corner point

(Cont. Next Page)

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T30-10

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,  
with brass cap mkd:

T 30 S  
R 10 W R 9 W  
S 1 | S 6  
S 12 | S 7  
1962

Fd. OK, June 1984 by R. Geisler - M 97-9

BLM retracement by Aaron M Graham, Cadastral Surveyor, under  
Group No 2164, surveyed June/Oct. 2007 - (DCSO records Vol.  
56 Page(s) 22256-8 and BLM Plat 2010-1 & 2010-2)

-----  
The cor. of secs. 1, 6, 7, and 12, on the W. bdy of the Tp.,  
perpetuated by Jelley in 1962; monumented with an iron post,  
2 1/2" dia., firmly set, projecting 6" above ground, with brass  
cap (properly) mkd.

from which the remains of the BTs mkd. by Bushey in 1893

A fir stump, 25" dia., bears N.7°E., 27.7 ft., with a  
healed blaze.

A fir, 39" dia., bears S.80°E., 16.9 ft., with a healed  
blaze. (Record, S.79°E., 9.5 ft.)

A fir, 27" dia., bears S.38 3/4°W., 29.5 ft., with a healed  
blaze. (Record, S.39 1/2°W., 32.3 ft.)

A fir, 25" dia., bears N.60°W., 18.4 ft., with a healed  
blaze. (Record, 22.4 ft.)

and a bearing object mkd. by person(s) unknown

A rock face bears S.29 1/2°W., 25.4 ft., with X chiseled in  
vertical face.