

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & Sec. 1, T30-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page 7377)

Set ¼ sec. post, from which
A Cedar 24" dia., bears N.5°E., 27 lks. dist.
A Cedar 24" dia., bears N.10°W., 87 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page 7408)

Set a stone 14x10x10 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Hemlock 10" dia., bears N.77°E., 16 lks. mkd. ¼ S BT.
A Hemlock 12" dia., bears N.73½°W., 7 lks. mkd. ¼ S BT.
After diligent search, I am unable to find either the old ¼ sec. cor. or the witness trees.

Survey by Bruce A. Shaner - For: Evans Products - Jan/April 1963 - RM 1-36

Found no evidence of any earlier surveys, so as per instructions by letter from the Area Cadastral Engineer, Mr. Tillman, dated March 29, 1963, I SET the ¼ corner by proportional measurement, using Bushey's 1893 retracement figures and the Hathorn Township corner.
Set 5/8" x 36" Iron rod, from which a:
8" Hemlock, I scribed "¼ S S1 BT", bears N.80°W., 55.4 ft.
16" P.Orford Cedar, I scribed "¼ S S6 BT" bears N.34°E., 60.4 ft.

Survey by Ronald Geisler, LS #1988 - For: Champion International Corp. - May/June 1984 - M 97-9

Found - A 5/8" Iron rod set by Shaner in the correct position.
1963 BT, a 11" Hemlock bears N.80°W., 54.6 ft. (Rec. 55.4 ft.) with healed face.
Replaced Iron rod with an alum. cap 2½" on a 7/8" x 36" I.P. Cap properly stamped and also with PLS 1988. Drove the iron rod alongside the iron pipe.
New BT - 9" Hemlock bears East, 26.1 ft. scribed ¼ S6 BT.

Coos County Surveyors Office - Michael Dado, Surveyor - Crew: Matthew Martin & Bill Hales - 11/18/2014 - C.S. File 65/87-19

Condition Report only
We find a 2½ alum cap on a 7/8" iron pipe, per Geisler, 1984
16" White Cedar stump, N.34°E., 61.20' cont next pg

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & Sec. 1, T30-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" Hemlock stump, N.79°W., 54.32'
17" D.Fir, N.77°30'E., 16.60'
14" D.Fir, S.37°30'W., 12.86'
15" D.Fir, N.66°30'W., 5.28'
12" D.Fir, N.14°E., 9.67'
Dec. 17°E