

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7439)

Set a stone 16x8x8", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
 A cedar, 18" dia., bears N.4½°W., 16 lks., mkd: ¼ S BT.
 A hemlock, 24" dia., bears S.82°W., 94½ lks., mkd: ¼ S BT.

Mark Smalley - For: Roseburg Forest Products - Feb. 1994 - M 119-18

Found - 5/8" iron rod (No rec) and original stone marked "¼"
 18" Cedar, N.4½°W., 10.6 ft. rotten snag.
 10" Fir, N.76°E., 3.2 ft. scribe visible.
 50" fir, N.89¼°W., 20.3 ft. scribe visible, original line tree. Notes call for it on line east of corner. Tree was faced and scribed by GP survey.
Scribed- 8" Fir, N.27°W., 9.7 ft. "¼ BT"
 8" Fir, S.41°W., 7.4 ft. "¼ BT"