

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613,
dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7442)

A solid rock 8'x7'x6' above ground which I mark for ¼ sec.
cor. with a cross (+) at exact cor. point & ¼ on N. face,
from which

A hemlock, 12" dia., bears S.62½°W., 40 lks., mkd: ¼ S BT.

A cedar, 38" dia., bears N.17½°E., 49½ lks., mkd: ¼ S BT.

Mark Smalley, Roseburg Forest Products - Feb. 1994 - M119-18

Found - Original stone, 8'x7'x6' marked ¼ on north, and 'X'
on top.

38" Cedar, N.17½°E., 32.7 ft. stump, orig. BT.

Scribed- 8" Fir, N.4°W., 13.4 ft. "¼ BT"

14" Fir, N.41°E., 15.5 ft. "¼ BT"

12" Fir, EAST, 13.0 ft. "¼ BT"

10" Fir, S.54°W., 14.8 ft. "¼ BT"