

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7452)

Set a stone 12x10x5", 8" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which

A fir, 5" dia., bears S.46°E., 119 lks., mkd: 1/4 S BT.

A fir, 12" dia., bears N.64°E., 311 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #477 surveyed July 1962 - (DCSO records Vol. 31 Page(s) 13176)

The sec. cor. of secs. 6 & 7, determined at record bearing and distance from the original bearing trees:

A fir, 32" dia., bears N.64°E., 311 lks., with a healed blaze.

A fir snag, 72" dia., bears S.46°E., 119 lks., with scribe marks S visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked

1/4 $\frac{S\ 6}{S\ 7}$

T30S R9W

1962

from which new BTs

A fir, 15" dia., bears N.35°W., 42 lks., mkd: 1/4 S6 BT.

A fir, 20" dia., bears S.42 1/2°E., 8 lks., mkd: 1/4 S7 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - Oct. 1965 - C.S. File 53/53-11

Found - Brass cap at cor. mkd: T30S R9W 1/4 $\frac{S\ 6}{S\ 7}$ US DEPT.

1962

OF INTERIOR

22" D.Fir, S.42 1/2°E., 8 lks., 1/4 S6 BT.

13" D.Fir N.35°W., 42 lks., 1/4 S7 BT. This tree rotten in trunk & cracked. Also in area of a lot of blow down.

Orig. 5" fir S.46°E., 78.5 ft. tree opened, no scribe visible.

Do not find NE BT.

New BT - 20" D.Fir N.44°E., 16.7 ft. scribed 1/4 S6 CS BT.

Fd. Ok by H. Johnstone, 1/15/1981 - M86-63

Fd. Ok 6/1984, R. Geisler, M97-9