

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7437)

Set a stone 15x11x10", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A fir, 36" dia., bears S.74¼°E., 11 lks., mkd: ¼ S BT.
 A fir, 33" dia., bears S.42°W., 27 lks., mkd: ¼ S BT.

Eugene Bloom - For: Roseburg Lumber Co. - March 6, 1980 - M79-23

Found - Original 33" Fir, now a stump, bears S.42°W., 17.8 ft with visible scribe "¼ BT".
 No trace of S32 BT, but did find large root hole.
Set - 1½" iron pipe with brass cap.
New BTs- 6" Madrone bears S.39°W., 50.6 ft scribed "¼ S31 BT"
 6" Chinquapin bears N.68°E., 56.0 feet scribed "¼ S32 BT".