TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7440)

---

Set a stone 13x12x5", 9" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 4" dia., bears S.67½°E., 26½ lks., mkd: ¼ S BT.
A cedar, 32" dia., bears S.32¾°W., 31½ lks., mkd: ¼ S BT.

---

Douglas Co. Surveyors Office - John M. Powell - J. Brady & F. Jones - Nov. 1965 - C.S. File 53/53-16

---

Found - No trace of stone set at corner.
4' Doug. Fir stump S.67½°E., 17.5 ft., opened stump for scribe "S"
32" cedar stump S.32¾°W., 20.8 ft, scribe visible.
Set brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1965
T30S R9W ¼ S30|S29
New BTs- 4" D.Fir S.18½°E., 10.7 ft. scribed ¼ S CS BT.
5" D.Fir S.30°W., 13.9 ft. scribed ¼ S30 CS BT.

---

Mark Smalley - For: Roseburg Forest Products - Feb. 1994 - M 119-18

---

Found - County Brass cap/iron pipe. 1965
48" Fir stump, S.67½°E., 117.5 ft. scribe visible, orig. BT
8" Fir, S.18½°E., 10.7 ft. healed face.
32" Cedar stump, S.32¾°W., 20.8 ft. scribe visible, orig. BT.
10" Fir, S.30°W., 13.9 ft. healed face.
Scribed- 8" Fir, N.19°W., 8.3 ft. "1/4 S30 BT"
11" Fir, N.55°E., 19.0 ft. "1/4 S29 BT"

---