

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor Secs 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7441)

Set a stone 12x12x6", 8" in the ground for cor. of secs. 19, 20, 29, & 30 mkd with 2 notches on S & 5 notches on E edges, from which

A fir, 10" dia., bears N.23 $\frac{3}{4}$ °E., 57 $\frac{1}{2}$ lks., mkd: T30S R9W S20 BT.

A fir, 14" dia., bears S.54°E., 72 $\frac{1}{2}$ lks., mkd: T30S R9W S29 BT.

A hemlock, 12" dia., bears S.24 $\frac{1}{2}$ °W., 65 lks., mkd: T30S R9W S30 BT.

A fir, 15" dia., bears N.71 $\frac{1}{4}$ °W., 64 lks., mkd: $\frac{1}{4}$ S19 BT.

Douglas Co. Surveyors Office - John M. Powell - Joe Brady - Oct. 1965 - C.S. File 53/53-1

Found - Stone at corner, 5 notches on East face.
Orig. 10" now 22" Fir N.24°E., 38.9 ft.
Orig. 14" now 35" Fir S.54°E., 49.2 ft.
Orig. 15" now 32" Fir N.71 $\frac{1}{2}$ °E., 42.4 ft.
(all BTs above are standing & have good scars)
12" hemlock S.24 $\frac{1}{2}$ °W., 42.9 ft. stump shows scribing "T S R9W"

Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R9W S19|S20
OFFICE 1965 S30|S29

New BT - 36" D.Fir S.82°W. 37.8 ft scribed T30S R9W S30 CS BT

Mark Smalley - For: Roseburg Forest Products - Feb. 1994 - M 119-18

Found - 1965 County Brass cap/iron pipe.
38" Fir, N.71 $\frac{1}{4}$ °W., 42.2 ft. healed face, orig. BT.
22" Fir, N.23 $\frac{3}{4}$ °E., 38.9 ft. healed face, orig. BT.
40" Fir, S.54°E., 49.2 ft. healed face, orig. BT.
54" Fir, S.82°W., 67.8 ft. healed face.
14" Cedar, N.46°E., 26.0 ft. "X" blazed on tree.

Fd. Ok by G. Smither, Jan. 2001 - M136-54