TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION ¼ Cor. Secs. 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7443)

Set a stone 16x12x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 30" dia., bears N.80½°E., 17 lks., mkd: ¼ S BT.
A fir, 32" dia., bears S.53¼°W., 13¾ lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - H.L. Eppstein - For: A.P. Sweet - June 6, 1930 - C.S. File 37/32
Found - Identified corner from rock & 1 OBT as recorded govt. field notes.
New BTs- 14" Hemlock N.88¾°W., 53 lks., slope 27°20'
26" Fir, N.21¾°E., 57 lks., slope 24°10', scribed ¼ S20 CS BT.

Gary Smither - For: Moore Mill Co. - Jan. 2001 - M136-54

No trace of orig. Proportioned between orig. line tree & SW corner of Sec. 20. (See narrative)
Set - 5/8"x30" IR w/2" alum. cap mkd: T30S R9W

¼
S19 | S20
2001
LS 2485

10" D.Fir N.24°W., 14.5 ft. to spike side center scribed ¼ S19 BT with alum. tag.
10" D.Fir N.69°E., 12.9 ft. to spike side center scribed ¼ S20 BT with alum. tag.
8" D.Fir S.23°E., 21.0 ft. to spike side center scribed ¼ S20 BT with alum. tag.
8" D.Fir S.12°W., 7.6 ft. to spike side center scribed ¼ S19 BT with alum. tag.