

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7447)

-----  
Set a stone 14x12x12", 10" in the ground for cor. of secs. 7, 8, 17, & 18 mkd with 4 notches on S & 5 notches on E edges, from which

A fir, 20" dia. bears N.30°E., 74 lks. mkd: T30S R9W S8 BT  
A cedar, 11" dia., bears S.56½°E., 18 lks., mkd: T30S R9W S17 BT.

An Oak, 14" dia., bears S.8¾°W., 68½ lks., mkd: T30S R9W S18 BT.

A fir, 20" dia., bears N.48¼°W., 30½ lks., mkd: T30S R9W S7 BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #477 surveyed July 1962 - (DCSO records Vol. 31 Page(s) 13172-3)

-----  
The cor. of secs. 7, 8, 17, & 18 is determined at record bearing & dist. from the remaining orig. BTs:

A sawed fir stump 30" dia., bears N.30°E., 74 lks., with bottom of healed blaze.

A fir, 30" dia., bears N.48¼°W., 30½ lks. with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 21" in the ground, and in a mound of stone, 3 ft. base to top, with brass cap marked

T30S	R9W
S 7	S 8
S 18	S 17
1962	

from which new BTs:

A cedar, 11" dia., bears N.27½°E., 35 lks., mkd: T30S R9W S8 BT.

A cedar, 13" dia., bears S.38°E., 239 lks., mkd: T30S R9W S17 BT.

A fir, 13" dia., bears S.57°W., 121 lks., mkd: T30S R9W S18 BT.

A fir, 33" dia. bears N.71°W., 87 lks. mkd: T30S R9W S7 BT

BLM dependent resurvey by Herman A. Pieske, Land Surveyor #1651 under contract No YA-553-CT2-67 under group #1107 surveyed July 1982/Feb. 1983 - (DCSO recs Vol. 48 pgs 18299-18300)

-----  
The cor. of secs 7, 8, 17, & 18, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, and in a mound of stone, 2½ ft. base, to top, with brass cap (properly) mkd. continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of two original bearing trees  
A sawed fir stump, 30" dia., bears N.30°E., 74 lks., with the bottom of part of a healed blaze.  
A fir snag, 32" dia., bears N.48¼°W., 30½ lks., with a healed blaze.  
and bearing trees mkd. by Jelley in 1962  
A cedar, 15" dia. bears N.27½°E., 35 lks with healed blaze  
A cedar, 13" dia., bears S.38°E., 239 lks., with scribe marks T30S R9W S17 BT visible on an open blaze.  
A fir, 15" dia., bears S.57°W., 121 lks. with healed blaze  
A fir, 34" dia., bears N.71°W., 87 lks., with healed blaze  
and new bearing trees  
A live oak, 4" dia., bears S.89°E., 32 lks., mkd. X BT.  
A fir, 7" dia., bears S.5°W., 51 lks., mkd. X BT.

BLM retracement by Aaron M Graham, Cadastral Surveyor, under Group No 2164, surveyed June/Oct. 2007 - (DCSO records Vol. 56 Page(s) 22256-8 & BLM Plats 2010-1 & 2010-3)

-----  
The cor. of secs. 7, 8, 17, & 18, perpetuated by Jelley in 1962, rehabilitated by Pieske in 1982; monumented with on iron post, 2½" dia., firmly set, with top flush with the surface of the ground, with brass cap (properly) mkd. from which an original bearing tree  
A fir, 38" dia., bears N.48¼°W., 18.4 ft., with a healed blaze. (Record, 20.1 ft.)  
and the remains of the bearing trees mkd. by Jelley  
A cedar, 20" dia., bears N.27½°E., 21.7 ft., with a healed blaze. (Record, 23.1 ft.)  
A cedar, 16" dia. bears S.38°E. 157.7 ft with healed blaze  
A fir snag, 30" dia., bears N.71°W., 57.4 ft.. with a healed blaze.  
and a bearing tree mkd. by Pieske  
A fir, 15" dia., bears S.5°W., 32.5 ft., with a healed blaze. (Record, 33.7 ft.)

Kris DeGroot - For: Silver Butte Tmbr Co. - 6/2014 - M168-22

-----  
Found - 2½" iron post by Jelley, USBLM Cadastral Surveyor, 1962, firmly set, flush with the ground, with a 2½" brass cap properly mkd. From which a BT by Jelley in 1962:  
A 16" cedar bears S.38¼°E., 108.1 ft. With a healed blaze. (Rec. S.38°E., 157.7 FT.  
All other BTs as reported by Graham & Felker under a 2010 USBLM dependent resurvey.