

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6 (RM)

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7454)

Set a stone 14x10x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A cedar, 7" dia., bears N.76½°W., 36¼ lks., mkd: ¼ S BT.

A fir, 8" dia., bears S.36½°E., 38¾ lks., mkd: ¼ S BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #477 surveyed July 1962 - (DCSO records Vol. 31 Page(s) 13177-8)

The ¼ sec. cor. of secs. 5 & 6, determined at record bearing and distance from the remaining original BT, falls in a creek, 25 lks. wide, course W., where it is impracticable to establish a standard monument. The original bearing tree,

A down fir, 20" dia., bears S.36½°E., 38¾ lks., with fragmentary scribe marks visible on opened blaze.

At the corner point

Drive a steel rod, 40" long, 5/8" dia., 28" in the creek bed to solid rock, from which new BTs and a reference monument:

A fir, 19" dia., bears N.29°E., 93 lks., marked ¼ S5 BT.

A hemlock, 10" dia., bears S.23¾°W., 45 lks., mkd ¼ S6 BT.

An iron post, 28" long, 2½" dia., set 25" in the ground, for a reference monument, bears S.45°W., 50 lks., with brass cap marked RM1 S6 1962 and an arrow pointing to the corner.

Ronald Stuntzner - For: Dept. of the Interior (BLM) - Aug. 8, 1980 - M85-18

Reference monument

Found - 1962 GLO Reference monument brass cap iron pipe from

which ¼ S6|S5 bears N.45°E., 50 lks. (33.0 ft.)

12" Hemlock bears S.24°W., 45 lks. (29.7 ft.)

Orig. Fir, now down with visible opened face bears S.36½°E., 38.7 lks.

Set - 3" Boat spike in bedrock at corner location.

BLM dependent resurvey by Randolph E. Younis, Cadastral Surveyor, under Group No. 2849 - surveyed Sept. 2016/March 2017 - (DCSO Records Vol. 59 Page(s) 23626)

The ¼ sec. cor. of secs. 5 & 6, determined at record bearings and distances from the accessories established by Jelley in 1962,

A fir, 32" dia., bears N.29°E., 61.4 ft., with a healed blaze.

Continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6 (RM)

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

A hemlock, 23" dia., bears S.23 $\frac{3}{4}$ °W., 29.7 ft., with a healed blaze.

An iron post, 2 $\frac{1}{2}$ " dia., firmly set, projecting 2" above ground, bears S.45°00'00"W, 33.00 ft., with a brass cap mkd. RM S6 1962 and an arrow pointing to the cor. Add marks 33.0 FT TO COR 2016 to brass cap.

At the corner point

Set an iron rod, 24" long, $\frac{5}{8}$ " dia., 24" in the ground, 12" of which are solid rock, flush with ground, in a collar of stone, with aluminum cap mkd.

T 30 S R 9 W

$\frac{1}{4}$
S 6 | S 5
2016