

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; & 5, T31-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7383)

Set ¼ sec. post, from which
A Fir 18" dia., bears S.5°E., 10 lks. dist.
A Fir 20" dia., bears N.73°E., 10 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7400)

This ¼ sec. cor. is burned. I find the witness trees. At Cor. point, I set a stone 14x10x4 ins., 9" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which
A Fir 18" dia., bears S.5°E., 10 lks. dist. mkd. ¼ S BT
A Fir 20" dia., bears N.73°E., 10 lks. dist. mkd. ¼ S BT.
These trees are both dead, I therefore mark 2 new witness trees:
A Fir 18" dia., bears S.33 3/4°E., 26½ lks. dist. mkd. ¼ S BT.
A Fir 30" dia., bears N.14¼°W., 128 lks. dist. mkd. ¼ S BT.

Survey by F.J. LaFlamme - For: Georgia Pacific - Dec. 2, 1966 - C.S. File 55/23

Found Original stone and 2 orig. BTs, now snags.
Scribe 2 BTs for this corner:
D.Fir 22", S.12°W., 34.7 ft. "¼ S5 BT 473"
D.Fir 22" N.25°E., 13.5 ft. "¼ S32 BT"

Douglas Co. Surveyors Office - John M. Powell, and crew - May 16, 1967 - C.S. File 53/53-39

Found - Orig. 24" D.Fir now snag, S.37°E., 17.8 ft., scribe visible.
24" D.Fir S.10°E., 34.0 ft. mkd. ¼ S5 BT.
24" D.Fir N.26°W., 13.5 ft. mkd. ¼ S32 BT.
Post at ¼ corner. Tagged all BTs by LaFlamme in 1966
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 9 W
¼ $\frac{S\ 32}{S\ 5}$
T 31 S R 9 W
1967

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Stephen J. Flause, Deputy -
Wit: T. Plouff; K. Mosley - April 7, 1981 - C.S. 61/19-32

Found - 1967 DCSO brass cap, properly mkd., on a 1" I.P.
firmly set and protruding 6" from ground.
1893 stone, measuring 14"x10"x4" is deposited on top
of ground and set on the E. side of the brass
cap. Stone is mkd. ¼ on its top side. (Rec. ¼ on
N. face)
A steel fence post protrudes 36" from the ground on
the W. side of the brass cap monument.
Possible remains of orig. SE. 18" Fir are found near
record brg. & dist.
No evidence of the other orig. BT is found.
1893, A Fir 18" is now a burned D.Fir snag 18" DBH,
approx. 35 ft. tall, bears S.34°E., 17.5 ft.,
face measurement (Rec. S.33 3/4°E., 17.5 ft.)
Tree has good evidence of burned blazes. No
scribing visible.
1893, A Fir 30" now the remains of a large burned
and rotted Fir stump, bears N.14¼°W., 84.5 ft.
No blazes or scribing apparent, rotted away.
A D.Fir 22" now a dead 26" DBH D.Fir, bears S.10°W.,
34.7 ft. (Rec. S.12°W., 34.7 ft.) Tree has burned
open blaze with no legible scribing. (1966)
A D.Fir 22" now a 38" DBH D.Fir, dead, bears
N.25°E., 13.5 ft. An opened blaze has the
scribing ¼ S32 visible. (1966)

Monument is accepted as found.

New Accessories:

A boat spike in a 12" dia 12" tall burl'd Fir stump,
bears N.06 3/4°W., 9.3 ft. Boat spike driven into
the top of said stump is stamped BO 2.
A spike in a D.Fir stump 20" dia and 21" tall, bears
S.59½°W., 42.1 ft. Spike is stamped BO 1.
An 8" DBH Madrone bears N.16°W., 81.9 ft. and is
bark scribed ¼ S32 CS BT.

All accessories are tagged with DCSO BT tags.

Fd. OK, Sept. 23, 1992 by DCSO - C.S. File 64/32-6