

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7438)

Set a stone 18x12x6", 13" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
 A fir, 17" dia., bears S.3°W., 35 lks., mkd: ¼ S BT.
 A fir, 40" dia., bears N.54°E., 14½ lks., mkd: ¼ S BT.

Eugene Bloom - For: Roseburg Lumber Co. - March 6, 1980 - M79-23

Found - Original BT, 17" fir, now a snag, bears S.7°W (S.3°W.) 23.1 ft with visible scribe "¼S".,
 Original BT, 40" fir, now a stump, bears N.58°E, (N.54°E.) 9.6 ft with visible scribe "¼ S BT".
Set - 1½" Iron pipe with brass cap.
New BTs- 6" D.Fir bears N.13°E., 26.3 ft scribed ¼ S29 BT.
 50" D.Fir bears S.14°E., 29.8 ft scribed ¼ S32 BT.