TOWNSHIP 30 RANGE 9 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7441-2)

Set a stone 16x12x10", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A hemlock, 6" dia., bears S.35½°E., 12 lks., mkd: ¼ S BT.
A chinquapin, 10" dia. bears N.49¼°E., 75 lks. mkd: ¼ S BT

Douglas Co. Surveyors Office - John M. Powell - F. Jones & J. Brady - Oct. 1965 - C.S. File 53/53-5

Found - 16x12x10 stone mkd: "¼"
6" now 14" hemlock S.35½°E., 12 lks., tree opened showing "¼" scribed.
10" Chinq. N.49°E., 75 lks., no trace.
Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R9W ¼ S 20
OFFICE 1965 S 29
New BTs- 18" chinq. S.78°W., 24.5 ft. scribed ¼ S2 CS BT.
40" D.Fir N.29°E., 41.6 ft. scribed ¼ S2 CS BT.
Note - This corner is about 100 ft. off top of ridge.

Fd. Ok G. Smither 1/2001 - M136-54