

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 17

Alias	Description

BLM dependent resurvey by Herman A. Pieske, Registered Land Surveyor #1651 under contract No. YA-553-CT2-67, under group #1107, surveyed July 1982/Feb. 1983 - (DCSO records Vol. 48 page(s) 18301)

Point for the center ¼ sec. cor. of sec. 17, at intersection with the E & W center line.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with aluminum cap marked:
T30S R9W
C ¼ S 17
1982

from which
A fir, 9" dia., bears S.59°W., 21 lks., mkd: C¼ S17 BT.
A fir, 8" dia., bears N.54°W., 24 lks., mkd: C¼ S17 BT.

Ken Hoffine - For: Lone Rock Timberland Co. and Roseburg Resources Co. - June 2011 - M162-78

Found - 1982 BLM cap
17" D.Fir bears S.59¾°W., 13.6 ft (record S.59°W., 13.86 ft.) BLM tag and healed face.
15" D.Fir bears N.57°W., 15.8 ft (record N.54°W., 15.84 ft.) No tag and healed face.
Corner lies on north slope in 40 year old thinned timber in In small depression.

BLM dependent resurvey by Randolph E. Younis, Cadastral Surveyor, under Group No. 2849 - surveyed Sept. 2016/March 2017 - (DCSO Records Vol. 59 Page(s) 23622)

The center ¼ sec. cor. of sec. 17, monumented with an aluminum post, 2½" dia., firmly set, projecting 9" above ground, with an aluminum cap (properly) mkd.
from which the remains of a BT mkd. by Pieske in 1982-83
A fir high stump, 18" dia., bears S.59°W., 13.9 ft., with a healed blaze.
and new bearing trees
A fir, 14" dia., bears N.34¼°E., 78.4 ft., mkd. C¼ S17 BT.
A fir, 14" dia., bears N.51¼°W., 60.9 ft., mkd. X BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.