TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7448)

Set a stone 16x12x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
An Oak, 6" dia., bears N.75°E., 95 lks., mkd: ¼ S BT.
An Oak, 12" dia., bears S.59½°E., 141 lks., mkd: ¼ S BT.

Reported as not found by DCSO 11/1965 - C.S. File 53/53-15

BLM dependent resurvey by Herman A. Pieske, Registered Land Surveyor #1651 under contract No. YA-553-CT2-67, under group #1107, surveyed July 1982/Feb. 1983 - (DCSO records Vol. 48 page(s) 18300)

Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor. Set an aluminum post, 28", long, 2½" dia., 24" in the ground, with aluminum cap mkd. T30S R9W

¼ S 8 / S 17

1982

from which
A fir, 10", bears N.9°E., 5 lks., mkd. ¼ S8 BT.
A cedar, 11", bears S.66½°E., 13½ lks., mkd. ¼ S17 BT.

Fd. Ok by D. Edwards, June 2003 - M142-38
Fd. Ok by K. DeGroot, Jan. 2008 - M154-76