

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7451)

-----

Set a stone 16x12x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

- A hemlock, 26" dia., bears N.21¼°W., 36½ lks. mkd: ¼ S BT.
- A yew, 12" dia., bears S.55°W., 19½ lks., mkd: ¼ S BT.

West 0.17 chs

- A fir, 6 ft. dia., on line marked with 2 notches on E & W sides.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #477 surveyed July 1962 - (DCSO records Vol. 31 Page(s) 13175-6)

-----

The sec. cor. of secs. 5 & 8, determined at record bearing and dist. from a line tree marked by Wm. M. Bushey, in 1893:

- A fir, 65" dia. bears West, 17 lks., with 2 notches each on E. and W. sides.

The corner has been obliterated by logging operations; the only other remaining evidence is the yew bearing tree in Sec. 8, 14". dia., fallen and dozed out of position, with axe marks indicating the old blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap marked:

¼  $\frac{S \ 5}{S \ 8}$

T30S R9W

1962

from which new BTs

- A fir, 6" dia., bears N.3½°W., 20½ lks., mkd: ¼ S5 BT.
- A cedar, 4" dia., bears S.55°E., 34 lks., mkd: ¼ S8 BT.

Fd. Ok by R. Stuntzner, 1/1981 - M87-20

BLM dependent resurvey by Randolph E. Younis, Cadastral Surveyor, under Group No. 2849 - surveyed Sept. 2016/March 2017 - (DCSO Records Vol. 59 Page(s) 23620-1)

-----

The ¼ sec. cor. of secs. 5 & 8, monumented with an iron post, 2½" dia., firmly set, projecting 15" above ground, with a brass cap (properly) mkd.

from which new accessories

- A hemlock, 21" dia., bears N.57½°E., 36.2 ft., mkd ¼ S5 BT
- An iron rod, 24" long, 5/8" dia., set 24" in the ground for a reference monument, bears N.43°26'04"W, 20.25 ft., with aluminum cap mkd. RM T30S R9W ¼ S5 20.2 FT TO COR 2016 and an arrow pointing to the cor. Cont.

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this cor., the remains of an original line tree recovered by Jelley in 1962 bears S.89°13'37"W., 11.2 ft., monumented with a burnt fir stump, 54" dia., no marks visible