

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 240640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald Stuntzner - For: Dept. of the Interior (BLM) - Aug. 8, 1980 - M85-18

-----

Set - 2" x 2" x 36" Cedar hub from which:  
26" Hemlock bears S.35°W,, 19.9 ft. to spike, 21.2 ft. øtree.  
12" Hemlock bears N.23°E., 13.2 ft. to spike, 14.2 ft. ø tree.

BLM dependent resurvey by Randolph E. Younis, Cadastral Surveyor, under Group No. 2849 - surveyed Sept. 2016/March 2017 - (DCSO Records Vol. 59 Page(s) 23624)

-----

The center ¼ sec. cor. of sec. 5, established by Stuntzner, in 1980; and is accepted as the cor.; determined at record bearing and distance from a bearing tree mkd. by Stuntzner  
A hemlock snag, 15" dia., bears N.83°E., 13.2 ft. to a spike in the root collar, with a bearing tree tag, and no other marks visible.

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with a brass cap mkd.

T 30 S R 9 W  
C ¼ S 5  
2016

from which new bearing trees  
A cedar, 18" dia., bears N.49°E., 9.9 ft., mkd. C¼ S5 BT.  
A hemlock, 10" dia., bears N.50°W., 27.0 ft., mkd C¼ S5 BT  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.