

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7382)

Marked a Laurel 15" dia. for cor. secs. 4, 5, 32 and 33, from which

- A Fir 10" dia., bears N.50°E., 10 lks. dist.
- A Fir 12" dia., bears S.60°E., 26 lks. dist.
- A Fir 12" dia., bears N.85°W., 60 lks. dist.
- A Fir 10" dia., bears S.30°W., 45 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7400-01)

The tree cor. is burned and also two of the witness trees. I find two of the witness trees. At cor. point, I Set a stone 18x10x10 ins., 13" in the ground for cor. to secs. 4, 5, 32 and 33, mkd. with 4 notches on E. and 2 notches on W. faces, from which

- A Fir 10" dia., bears N.50°E., 10 lks. dist. mkd. T30S R9W S33 BT.
- A Fir 12" dia., bears N.85°W., 60 lks. dist. mkd. T30S R9W S32 BT.

These are the original witness trees. I mark two new witness trees:

- A Fir 11" dia., bears S.85 3/4°E., 37 lks. dist. mkd. T31S R9W S4 BT.
- A Fir 33" dia., bears S.39 1/2°W., 77 lks. dist. mkd. T31S R9W S5 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 1965 - C.S. File 53/53-35

- Found - 10" D.Fir now 13", N.50°E., 6.6 ft. (should be 10.4 ft.). Shows good scar.
- 33" D.Fir now 40", S.39 1/2°W., 50.8 ft. (should be 48.8 ft.), shows fair scar.
- 11" D.Fir now 15", S.85 3/4°W., 24.4 ft., shows good scar.
- 12" Fir, down, N.85°W., 39.6 ft., opened for scribe "BT".

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S	R 9 W
S 32	S 33
S 5	S 4
1965	

(Cont. Next Page)

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec Cor for 32 & 33; 4 & 5, T31-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 34" D.Fir N.71°W., 42.5 ft. scribed T30S R9W S32 CS BT.
I could not find match dist. good so took 4 bearings and distances.

Ron Rice, NW Land Surveying - Jason Collver - June 2012 - C.S. File 65/77-5

Found - 2½ DCSO brass cap dated 1965
13" D.Fir, N.50°E, 6.6 ft., shows good scar- Missing
40" D.Fir, S.39½°W., 50.8 ft., shows fair scar -
Fd 40 stump with no marks
15" D.Fir, S.85¼°W. 24.4 ft. shows good scar-Missing
12" Fir, down, N.85°W., 39.6 ft., opened for scribe
"BT" - Missing
34" D.Fir, N.71°W., 42.5 ft., scribed T30S R9W S32
CS BT - Missing.

New - 11" D.Fir bears S.58°W., 31.0 ft. blazed, scribed
T31S R9W S5 BT
14" D.Fir bears N.79°W., 21.4 ft. blazed, scribed
T30S R9W S32 BT
13" D.Fir bears N.28°E., 25.8 ft. blazed, scribed
T30S R9W S33 BT
9" Madrone bears S.72°E., 3.7 ft. blazed, scribed
T31S R9W S4 BT

Note - Corner has steel post adjacent to it. All BTs have
red painted bands and yellow tags.
Compass decl. 16°E.