TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7424)

---

Set a stone 15x12x4", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 48" dia., bears N.65½°W., 37 lks., mkd: ¼ S BT.
A laurel, 12" dia., bears S.55½°E., 15 lks., mkd: ¼ S BT.
This cor. is on top of spur, course NW & SE.

Douglas Co. Surveyors Office - John M. Powell - F. Jones & J. Brady - Nov. 1965 - C.S. File 53/53-19

---

Found - 48" D.Fir now 57", N.65½°W., 24.4 ft. Opened & found scribing "S"
No trace of 12" laurel, S.55½°E., 9.9 ft.
Set brass cap at ¼ cor. mkd: COUNTY SURVEYORS OFFICE 1965
T30S R9W ¼ S29|S28
New BTs- 37" Laurel S.41°E., 42.0 ft. scribed ¼ S28 CS BT.

Fd. OK by K. Hoffine 4/1995 - M119-59