

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7425)

-----

Set a stone 18x10x8", 13" in the ground for cor. of secs. 20, 21, 28, & 29 mkd with 2 notches on S & 4 notches on E edges, from which

- A fir, 36" dia., bears N.12½°E., 38 lks., mkd: T30S R9W S21 BT.
- A fir, 20" dia., bears S.18°E., 18½ lks., mkd: T30S R9W S28 BT.
- A fir, 40" dia., bears S.65½°W., 21½ lks., mkd: T30S R9W S29 BT.
- A fir, 48" dia., bears N.53¾°W., 56½ lks., mkd: T30S R9W S20 BT.

Douglas Co. Surveyors Office - John M. Powell - F. Jones & J. Brady - Oct. 1965 - C.S. File 53/53-4

-----

Found - 36", now 40" Fir N.12½°E. 38 lks., shows good scar. (Tree now a snag.)

48", now 56" Fir N.53¾°W. 56½ lks., shows good scar. (Tree in good condition)

40", now 54" Fir S.65½°W. 21½ lks., shows good scar. (Tree now a snag)

20", now 26" Fir S.18°E. 18½ lks., opened tree for scribing (Tree now a snag.)

Set brass Cap at Cor. mkd: County Surveyors T30S R9W S20|S21 Office, 1965 S29|S28

New BTs- 56" Fir N.53¾°W. 37.3 ft. scribed T30 R9W S20 CS BT.  
4" Maple S.47°E. 11.9 ft., scribed S28 CS BT.  
6" Hemlock N.52°E. 39.5 ft., scribed S21 CS BT.

Note - Location of corner is in a small ravine on N. slope about 100 ft. south of bottom of ravine.

Fd. Ok by K. Hoffine, 4/1995 - M119-59

BLM retracement by Aaron M Graham, Cadastral Surveyor, under Group No 2164, surveyed June/Oct. 2007 - (DCSO records Vol. 56 Page(s) 22256-8 and BLM Plat 2010-1 & 2010-2)

-----

The cor. of secs. 20, 21, 28, & 29, perpetuated by Powell, in 1965, and utilized by Hoffine, in 1995; monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd. from which the remains of the original BTs

- A fir stump, 22" dia., bears N.12½°E., 25.1 ft., no marks visible.

continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir snag, 17" dia., bears S.16¼°E., 10.3 ft., with scribe marks BT visible on open blaze. (Record, S.18°E., 2.2 ft.)  
A fir stump, 50" dia., bears S.65½°W., 11.8 ft., with a healed blaze. (Record, 14.2 ft.)  
A fir, 55" dia., bears N.53¾°W., 37.3 ft., with a healed blaze.  
and the remains of a BT mkd. by Powell  
A roothole bears S.57¾°E., 11.6 ft., alongside of which is a down maple, 10" dia., with a healed blaze.  
and new bearing trees  
A hemlock, 12" dia., bears S.38½°E., 29.9 ft., mkd. T30S R9W S28 BT.  
A fir, 10" dia., bears S.43°W., 17.4 ft., mkd. T30S R9W S29 BT.  
No suitable trees available in the NE. quadrant.