

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7429)  
-----  
Set a stone 14x10x8", 9" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which  
    A fir, 30" dia., bears N.63°W., 24 lks., mkd: 1/4 S BT.  
    A fir, 30" dia., bears N.48 1/2°E., 42 1/2 lks., mkd: 1/4 S BT.

Reported as not found, DCSO VRT 10/1964 - C.S. File 53/53-70

Jack LaFlamme - For: Georgia Pacific - April 19, 1979 - C.S. File 58/249  
-----  
Found - 34" stump, (orig. 30" Fir BT) bears N.63°W., 24 lks. which has plain scribes.  
        34" stump, (orig. 30" Fir BT) bears N.48 1/2°E. 42 1/2 lks with plain scribes.  
Set - 3/4" brass cap pipe marked "GP 1/4 Cor 17|16 T30 R9 1979"  
New BTs- 16" Hemlock N.43°45'E. 59.7 ft scribed "1/4 S 16 BT 378"  
        16" Oak, N.29°45'W., 59.7 ft. scribed "1/4 S 17 BT" in the bark.

BLM dependent resurvey by Herman A. Pieske, Registered Land Surveyor #1651 under contract No. YA-553-CT2-67, under group #1107, surveyed July 1982/Feb. 1983 - (DCSO records Vol. 48 page(s) 18296-7)  
-----  
The 1/4 sec. cor. of secs. 16 and 17, perpetuated and recorded by LaFlamme, in 1979, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap (properly) mkd. from which the remains of the original bearing trees  
    A fir stump, 32" dia., bears N.48 1/2°E., 42 1/2 lks., with fragmentary scribe marks visible on an open blaze.  
    A fir stump, 36" dia., bears N.63°W., 24 lks., with fragmentary scribe marks visible on an open blaze.  
and bearing trees mkd. by LaFlamme  
    A fir, 16 1/2" dia., bears N.50°E., 92 lks., with fragmentary scribe marks visible on an open blaze.  
    A tan oak, 16" dia., bears N.29°W., 97 lks., with scribe marks 1/4 S17 BT visible on an open blaze.

BLM retracement by Aaron M Graham, Cadastral Surveyor, under Group No 2164, surveyed June/Oct. 2007 - (DCSO records Vol. 56 Page(s) 22256-8 & BLM Plats 2010-1 & 2010-3)  
-----  
The 1/4 sec. cor. of secs. 16 & 17, perpetuated by LaFlamme, in 1979, subsequently utilized by Pieske in 1982-83, cont.

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.

from which the remains of the original BTs

A fir stump, 30" dia., bears N.48½°E., 28.1 ft. no marks visible.

A fir stump, 35" dia., bears N.63°W., 15.8 ft. no marks visible.

and a BT mkd. by LaFlamme, and reported by Pieske

A fir, 24" dia., bears N.48¾°E., 60.7 ft., with a healed blaze. (Record, N.50°E.)

and a new BT

A fir, 11" dia., bears S.69½°W., 16.9 ft., mkd. ¼ S17 BT.