

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16 & 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7429-30)  
-----  
Set a stone 18x10x8", in mound of stone to prevent its being moved by horses & cattle, for cor. of secs. 8, 9, 16, & 17 mkd with 4 notches on S & E edges, from which  
A fir, 6" dia. bears N.60½°E., 46 lks. mkd: T30S R9W S9 BT  
A fir, 24" dia., bears S.17½°E., 187½ lks., mkd: T30S R9W S16 BT.  
A fir, 30" dia., bears S.50°W., 116½ lks., mkd: T30S R9W S17 BT.  
An Oak, 12" dia., bears N.66¾°W., 96 lks., mkd: T30S R9W S8 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - Oct. 1964 - C.S. File 53/53-69  
-----  
Found - 3 Orig. BTs. & Rock Mound. Corner Stone gone  
12", now 14" Oak N.66¾°W. 63.4 ft., shows good scar.  
30", now 40" Fir S.50°W. 76.9 ft., shows good scar, now snag.  
24", now 36" Fir S.17½°E. 123.8 ft., shows good scar.  
Set brass Cap at Cor in mound of stone mkd: T30S R9W S 8|S 9  
County Surveyor's Office, 1964 S17|S16  
New BTs- 14" W.Oak N.22°E. 21.9 ft. mkd: T30S R9W S9 CS BT.  
12" Laurel N.61°W. 19.4 ft mkd: T30S R9W S8 CS BT.  
9" W.Oak S.33°W. 49.1 ft. mkd: T30S R9W S17 CS BT.  
10" W.Oak S.42°E. 53.4 ft. mkd: T30S R9W S16 CS BT.

BLM dependent resurvey by Herman A. Pieske, Registered Land Surveyor #1651 under contract No. YA-553-CT2-67, under group #1107, surveyed July 1982/Feb. 1983 - (DCSO records Vol. 48 page(s) 18298)  
-----  
The cor, of secs. 8, 9, 16, & 17, perpetuated and recorded by Tracy, in 1964, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, and in mound of stone, 3 ft. base, to top, with brass cap (properly) mkd. from which the remains of the original bearing trees  
A fir snag, 42" dia., bears S.50°W., 116½ lks., with fragmentary scribe marks visible on an open blaze.  
A W.Oak, 14½" dia., bears N.66¾°W., 96 lks., with a healed blaze.  
and bearing trees mkd. by Tracy  
A W.Oak, 15" dia., bears N.32°E., 33 lks., with a healed blaze.  
continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16 & 17

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

A W.Oak, 9" dia., bears S.33°W., 74 lks., with a healed blaze.  
A madrone, 12" dia., bears N.61°W., 29 lks., with fragmentary scribe marks visible on a partially healed blaze.

Fd. OK by D.Edwards, June 2003 - M142-38

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2088, surveyed Aug. 2004/June 2005 - (DCSO records Vol. 54 Page(s) 21274-5)

-----  
The cor. of secs. 8, 9, 16, and 17, perpetuated by Tracy, in 1964, monumented with an iron post, 1" dia., firmly set, projecting 30" above ground, in a mound of stone, 3 ft. base, 1½ ft. high, with brass cap mkd.  
from which the remains of the original bearing trees  
A fir snag, 33" dia., bears S.50°W., 73.6 ft., with no marks visible on open burned blaze. (Record, 76.9 ft.)  
A white oak, 15" dia., bears N.66¾°W., 63.4 ft., with a healed blaze.  
and bearing trees mkd. by Tracy, reported by Pieske  
A white oak, 16" dia., bears N.23°E., 21.8 ft., with a healed blaze. (Record, N.32°E.)  
A white oak, 9" dia., bears S.32°W., 48.3 ft., with a healed blaze. (Record, S.33°W., 48.8 ft.)  
A madrone, 12" dia., bears N.59°W., 19.1 ft., with a healed blaze. (Record, N.61°W.)  
and a bearing tree mkd. by Tracy  
A white oak, 9" dia., bears S.39¾°E., 53.1 ft., with a healed blaze.

Fd. Ok by K. DeGroot, 1/2008 - M154-76