

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300515

PRIMARY CORNER DESCRIPTION AP 1 (Line tree) on line between 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, under contract #613 dated April 29, 1893 - (DCSO Records Vol. 18 Page 7432)

A cedar, 12" dia., on line marked with 2 notches on N & S sides.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2088, surveyed Aug 2004/June 2005 - (DCSO records Vol. 54 Page(s) 21275)

An orig line tree, a cedar, 30" dia., in good condition, mkd. with one notch on N side & two notches & an axe mark on S side. This now becomes angle point No. 1 between secs 8 & 9 From which a new reference monument and bearing tree

An aluminum rod, 36" long, ½" dia., set 33" in the ground for a reference monument, bears
N.45°00'00"E., 10.00 ft. with aluminum cap mkd. AP1 S9 RM 10.0 FT 2004 and an arrow pointing to the corner.

A fir, 14" dia. bears N.28¾°W., 22.1 ft., mkd. AP1 S8 BT Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description

fd. Ok by K. DeGroot, 1/2008 - M154-76