

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300528

PRIMARY CORNER DESCRIPTION AP 2 (Line tree) on line between 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, under contract #613 dated April 29, 1893 - (DCSO Records Vol. 18 Page 7432)

-----  
A fir, 4 ft. dia., on line marked with 2 notches on N & S sides.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2088, surveyed Aug 2004/June 2005 - (DCSO records Vol. 54 Page(s) 21276)

-----  
An original line tree, a fir, 62" dia., in good condition, mkd. with two notches each on N & S sides. This now becomes angle point No. 2 between secs. 8 & 9.

From which a new reference monument and bearing tree  
An aluminum rod, 36" long, ½" diam., set 28" in the ground for a reference monument, bears  
N.45°00'00"E., 10.00 ft. with aluminum cap mkd. AP2  
S9 RM 10.0 FT 2004 & an arrow pointing to the corner.

A fir, 10" dia., bears N.18¾°W., 59.4 ft. mkd. AP2 S8 BT  
Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description