

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7432-3)

Set a stone 14x14x8", 9" in the ground for cor. of secs. 4, 5, 8, & 9 mkd with 5 notches on S & 4 notches on E edges, from which

- A fir, 22" dia. bears N.83°E. 38½ lks. mkd: T30S R9W S4 BT
- A cedar, 20" dia., bears S.35¾°E., 69 lks., mkd: T30S R9W S9 BT.
- A fir, 14" dia. bears S.50°W. 46½ lks. mkd: T30S R9W S8 BT
- A fir, 60" dia. bears N.36½°W. 31 lks. mkd: T30S R9W S5 BT

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #477 surveyed July 1962 - (DCSO records Vol. 31 Page(s) 13174-5)

The cor. of secs. 4, 5, 8 & 9, monumented with the orig. basalt stone, 14x14x8", firmly set 10" in the ground, marked with 5 notches on the S & 4 on the E edges, from which the orig. BTs:

- A sawed fir stump, 35" dia., bears N.83°E., 38½ lks., with no marks remaining.
- A cedar, 22" dia., bears S.35¾°E., 69 lks. with scribe marks T30S R9 visible on partly healed blaze.
- A fir, 18" dia., bears S.50°W., 46½ lks., with a healed blaze.
- A fir, 70" dia., bears N.36½°W., 31 lks., with healed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T30S R9W
S 5 | S 4
S 8 | S 9
1962

from which a new BT,
A cedar 35" dia., bears N.12½°E., 36 lks., marked T30S R9W S4 BT.
Deposit basalt stone alongside the iron post.

Fd. Ok by R. Stuntzner 1/1981 - M87-20

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8 & 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor under Group #1023, surveyed July 1980- (DCSO records Vol. 45 Page(s) 17272-3)

The cor. secs. 4, 5, 8 & 9, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap properly mkd.

from which the remains of the orig. BTs
A sawed fir stump, 35" dia., bears N.83°E., 38½ lks., no marks remaining.

A root hole, bears N.36½°W., 31 lks., with a down fir alongside, 70" dia., with healed blaze.
and the remains of a BT mkd. by Jelley

A root hole, bears N.12½°E., 36 lks., with a down cedar alongside, 38" dia., with decayed blaze.

The corner is located in a logged area; no other suitable trees available within limits.

The geographic position of the corner of secs. 4, 5, 8 & 9, as determined by an indirect tie to USC & GS triangulation station "CAMAS 2" is as follows:

Latitude 42°58'56.3" N Longitude 123°46'48.2" W.

Gary Smithers - March 16, 2001 - C.S. File 65/37-4

Found - 1962 BLM brass cap on iron pipe firmly set alongside orig. stone monument.

All record BTs gone.

New BTs- 10" D.Fir, S.85°W., 15.7 ft. to spike driven in side center, mkd. "T30 R9 S8 BT" with BT tag.

7" D.Fir, S.71°E., 5.4 ft. to spike driven in side center, mkd. "X" @ breast height & "BT" at base, with BT tag.

12" D.Fir, N.68°E., 25.1 ft. to spike driven in side center, mkd. "T30 R9 S4 BT" with BT tag.

11" D.Fir, S.20°E., 18.8 ft. to spike driven in side center, mkd. "T30 R9 S4 BT" with BT tag.

Nothing was suitable for BT in Sec. 5.

BLM dependent resurvey by Randolph E. Younis, Cadastral Surveyor, under Group No. 2849 - surveyed Sept. 2016/March 2017 - (DCSO Records Vol. 59 Page(s) 23618)

Cor. of secs. 4, 5, 8, & 9, perpetuated by Smithers, in March 2001; monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with a brass cap (properly) mkd. from which the remains of the original bearing trees

A fir stump, 28" dia., bears N.83°E., 25.4 ft., with a healed blaze. Continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A badly decayed fir stump, 22" dia., bears S.50°W., 30.7 ft., with a healed blaze.
and the remains of the bearing trees mkd. by Smither
A decayed fir snag, 7" dia., bears S.70¾°E., 5.3 ft., with hacked X at breast height and scribe marks BT visible on partially healed blaze.
A fir, 15" dia., bears S.21¾°E., 18.9 ft., with a healed blaze.
A fir, 16" dia., bears S.82¾°W., 15.7 ft., with a healed blaze.
and new bearing trees
A chinquapin, 8" dia., bears N.62¾°E., 12.7 ft., mkd. T30S R9W S4 BT.
A fir, 16" dia., bears N.71¼°W., 38.4 ft., mkd. T30S R9W S5 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

The original basalt stone, 8x8", firmly set, projecting 10" above ground, with 5 notches on S. edge and 4 notches on E. edge, is alongside the cor.