

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7436)

-----

Set a Hemlock post, 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on W face; from which

A hemlock, 5" dia., bears N.74 1/2°W., 21 lks., mkd: 1/4 S BT.

A hemlock, 10" dia., bears S.44 1/2°E., 24 1/2 lks., mkd: 1/4 S BT

Ben B. Irving - Witnesses: LaVern Sutherlin, Herman Aydelot & T.L. Clinton Hyde - C.S. 37/115

-----

Identified by portion of orig. post mkd. 1/4 S and hole where it set also by 10" Hemlock S.43°30'E., 15.8 ft. 10" hemlock N.74°45'W., 13.6 ft. One of these BTs was only a rotten snag bearing scribe marks.

Set 4" cedar post for corner & marked a new BT.

A 12" hemlock S.43°15'E., 13.6 ft.

Searched for & not found 9/1964 & 10/1967 - C.S. 53/53-62

BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor under Group #1023, surveyed July 1980- (DCSO records Vol. 45 Page(s) 17273-4)

-----

Point for the 1/4 sec. cor. of secs. 4 & 5, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 24" in the ground with brass cap marked:

T30S R9W

1/4

S 5|S 4

1980

from which

A hemlock, 27" dia., bears N.57°E., 39 lks., mkd: 1/4 S4 BT.

A hemlock, 17" dia., bears S.74 1/2°W., 30 lks., mkd: 1/4 S5 BT

BLM dependent resurvey by Randolph E. Younis, Cadastral Surveyor, under Group No. 2849 - surveyed Sept. 2016/March 2017 - (DCSO Records Vol. 59 Page(s) 23625-6)

-----

The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 2 1/2" dia., firmly set, projecting 3 ins. above ground, with a brass cap (properly) mkd.

from which the remains of the BTs mkd. by Wofford in 1980

A hemlock stump, 31" dia., bears N.57°E., 25.7 ft., with illegible scribe marks visible on partially healed blaze.

Continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hemlock snag, 14" dia., bears S.73 $\frac{3}{4}$ °W., 19.2 ft., with scribe marks  $\frac{1}{4}$  S5 BT visible on partially healed blaze. (Record, S.74 $\frac{1}{2}$ °W., 19.8 ft.)  
and new bearing trees  
A hemlock, 12" dia., bears N.86 $\frac{1}{2}$ °E., 27.2 ft., mkd.  $\frac{1}{4}$  S4 BT.  
A hemlock, 9" dia., bears N.20 $\frac{1}{2}$ °W., 11.7 ft., mkd.  $\frac{1}{4}$  S5 BT.  
Each new BT has a 2 $\frac{1}{2}$ "x  $\frac{1}{4}$ " magnetic nail (Mag Nail) driven at the base right side-center & each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.