

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec 33; & 4, T31-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7382)

-----  
Set ¼ sec. post, from which  
A Fir 18" dia., bears S.45°W., 12 lks. dist.  
A Hemlock 24" dia., bears N.28°E., 33 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7401)

-----  
The ¼ sec.cor. and one witness tree are burned. The other witness tree is lying upon the ground, mkd. ¼ S BT. find the stump of this tree. At cor. point, I Set a stone 20x12x10 ins., 15" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which  
A Fir stump 18" dia., bears S.45°W., 12 lks. dist. mkd. on the tree of this stump "¼ S BT"  
I mark two new witness trees:  
A Hemlock 10" dia., bears S.79¼°E., 18½ lks. mkd. ¼ S BT.  
A Fir 36" dia., bears N.2¼°W., 22 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 1965 - C.S. File 53/53-36

-----  
Found - 20x12x10" stone with "¼" on N. face.  
36" Fir N.2½°W., 14.5 ft., blown down on face, shows two good faces.  
10" Hemlock now 21" S.79¼°E., 12.2 ft., shows scar, did not open, call very good on stream.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S  
¼  $\frac{S\ 33}{S\ 4}$  R9W  
T 31 S  
1965  
New BTs- 21" Hemlock S.79°E., 12.5 ft. scribed ¼ S4 CS BT  
56" Cedar N.38°E., 21.6 ft. scribed ¼ S33 CS BT.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 5/24/2005 - C.S. File 67/10-26

-----  
Found - Brass cap/iron pipe loose lying on top of ground.  
Fd. loose stone 18"x12"x6" w/mark "¼ visible on top of ground. Originally described as 20x12x10 stone, portions of stone are now broken off.  
continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec 33; & 4, T31-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

56" Cedar now 4 ft. tall x 48" dia., burnt stump scribing " /4 S33 CS BT" clearly visible on partly healed blazes bears N.38°E., 19.6 ft. (Rec. N.38°E., 21.6 agrees well as a slope dist.) 1965 BT

10" Hemlock now an approx. 6" tall x 18" dia., rotted stump no scribing fd. bears S.79°E., 12.5 ft. (1893 BT rescribed in 1965) (Agrees w/1965 rec.)

NW BT is fallen rotted Fir, root hole bears approx. N.2½°W., 14.5 ft. (agrees w/rec) 1893 BT

New - Reset BC/IP using rec. bearing & dist. from Hemlock stump & rec. bearing & slope dist. from burnt cedar stump.

Reset stone on South edge of BC/IP

9" dia., R.Cedar double blazed & scribed "¼ S4 CS BT" bears S.77°E., 18.9 ft.

13" dia., D.Fir double blazed & scribed "¼ S4 CS BT" bears S.6°E., 7.1 ft.

5" dia., D.Fir double blazed & scribed "X CS BT" bears N.6°E., 6.6 ft.

Comp. decl. 16¾°E.