

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7423)

-----  
Set a stone 12x10x5", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A chinquapin, 11" dia. bears S.45¼°W., 35 lks. mkd: ¼ S BT  
A fir, 52" dia., bears N.28½°E., 41 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Terry Connell - Sept. 1965 - C.S. File 53/53-13

-----  
Found - Orig. 52 now 55" Fir N.28½°E., 27.1 ft. open & shows "¼S" scribe.  
No trace of other BT or stone as called for.  
Set brass cap at cor. mkd: COUNTY SURVEYORS T30S R9W ¼ S 28  
OFFICE 1965 S 33  
New BT - 30" D.Fir S.12°W., 39.4 ft. mkd: ¼ S33 CS BT.  
Note - This corner lies on N top of cut bank on old logging road.

Ken Hoffine, L.S. #2291 - For: Lone Rock Timber Co. April 1995 - M 119-59

-----  
Found - County Brass cap 0.6' above ground.  
58" D.Fir, 20' tall snag bears N.29°E., 26.8', (Rec. N.28½°E., 27.1') chopped out face w/tag.  
30" D.Fir, 10' tall snag bears S.12°W., 39.9' (Rec. S.12°W., 39.4') scribing visible, w/tag.  
New BTs- 10" D.Fir, bears S.25°W., 41.9', scribed "¼ S33 BT" & tagged.  
10" hemlock, bears N.60½°W., 20.41', scribed "¼ S28 BT" & tagged.  
Corner lies on east side of a very shallow draw and 22 feet north of centerline of gravel road 30-9-28.1