

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7426)

Set a stone 16x12x6", 12" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
 A cedar, 8" dia., bears N.5°E., 26 lks., mkd: 1/4 S BT.
 A fir, 15" dia., bears S.1/2°E., 50 lks., mkd: 1/4 S BT.

Reported as not fd. DCSO 11/1965 - C.S. File 53/53-15

Ken Hoffine, L.S. #2291 - For: Lone Rock Timber Co. April 1995 - M 119-59

Set - 2" Alum. cap 0.5' above ground, stamped "LONE ROCK TIMBER 1/4 S21 S28 T30 R9 1995 PLS 2291"
 10" D.Fir bears S.72°W., 43.9', scribed "1/4 S28 BT" & tagged.
 9" D.Fir, bears N.44°W., 35.2', scribed "1/4 S21 BT" & tagged.
 10" Hemlock, bears S.47°E., 23.2', scribed "1/4 S28 BT" & tagged.
 10" Hemlock, bears N.36°E., 39.5', scribed "1/4 S21 BT" & tagged.
Corner lies on extremely steep, rocky, west facing slope, approx. 30' east of very old grown over road.

BLM retracement by Aaron M Graham, Cadastral Surveyor, under Group No 2164, surveyed June/Oct. 2007 - (DCSO records Vol. 56 Page(s) 22256-8 and BLM Plat 2010-1 & 2010-2)

The 1/4 sec. cor. of secs. 21 and 28, reestablished by Hoffine, in 1995, and is accepted as the corner, there is no remaining evidence of the original corner; monumented with an iron rod, 5/8" dia., firmly set, projecting 8" above ground, with aluminum cap (properly) mkd.
from which the remains of the bearing trees mkd. by Hoffine
 A hemlock snag, 11" dia., bears N.36°E., 39.5 ft., with illegible scribe marks visible on partially healed blaze.
 A hemlock, 13" dia., bears S.47 1/2°E., 23.2 ft., with illegible scribe marks visible on partially healed blaze.
 A fir, 12" dia., bears S.68 3/4°W., 44.1 ft., with a healed blaze.
 A fir, 12" dia., bears N.40 3/4°W., 35.3 ft., with a healed blaze.