TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7428)

Set a stone 12x10x10", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 6" dia., bears N.26½°W., 25½ lks., mkd: ¼ S BT.
A fir, 6" dia., bears S.5¾°E., 24½ lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - Oct. 1964 - C.S. File 53/53-49

Found - Rock 12x10x10" in place with "¼" on N. face.
6", now 14" D.Fir S.5¾°E. 16.1 ft., open & find "¼" scribe.
No trace of other BT.

Set brass Cap alongside Rock & Mkd: County Surveyors Off 1964
T30S R9W ¼ S 16 / S 21

New BTs- 30" D.Fir S.77°E. 32.3 ft. mkd: ¼ S21 CS BT.
20" D.Fir N.42°W. 65.6 ft. Mkd: ¼ S16 CS BT.

Note - This corner lies on steep, south slope approximately 100 ft. North of Creek.