

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 28" dia., bears N.9½°E., 13.2 ft., with a healed blaze. (Record, N.2°W.)
A roothole bears S.27°E., 20.3 ft., alongside of which is a down oak, 12" dia., no marks visible.
and the remains of the bearing trees mkd. by Tracy
A fir, 22" dia., bears N.53°E., 28.6 ft., with a healed blaze.
An oak snag, 23" dia., bears S.13¼°E., 33.0 ft., no marks visible.
and the bearing tree mkd. by Johnstone, in 1982
A madrone, 16" dia., bears S.57°W., 15.1 ft., with scribe marks /4 S BT and other illegible scribe marks visible on partially healed blaze and a nail in face with brass washer mkd. RLS 498.
Corner falls on top of cut bank on N. edge of old trail, 8 ft. wide, bears N. 75° E. and S. 60° W.

The geographic position (NAD 1983 (91)) of the quarter corner between sections 9 and 16, as determined from a tie to ODOT GPS station "WCAM", is as follows:
Latitude: 42°58'03.43"N. Longitude: 123°46'16.46"W.

From this point, the GPS control station "WCAM", established by ODOT in 1989, at latitude 43°00'36.90832"N. and longitude 123°41'58.63498"W. (NAD 83 (91)), bears N.50°57'41"E., 24,671.02 ft. (mean bearing and sea level distance), monumented with an aluminum cap, with top 13 ins. below the surface of the ground, mkd. 1989 WCAM, in a collar of concrete.