TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7434)

Set a stone 18x14x10", 13" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 16" dia., bears N.62¼°W., 56¾ lks., mkd: ¼ S BT.
A fir, 10" dia., bears S.78¾°W., 39½ lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - F. Jones & J Brady - Oct. 1965 - C.S. File 53/53-6

Found - 16" fir stump N.62°W., 56¾ lks., stump opened showing "¼" scribe.
10" fir, fd to be 7", S.78¾°W., 39½ lks., tree is dead but shows scribing "¼S BT"
Set brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1965 T30S R9W ¼ S 4 / S 9
Set cap in mound of stones on rock point.
New BTs- 15" D.Fir N.54°W., 47.0 ft. scribed ¼ S4 CS BT.
20" D.Fir S.86°W., 40.6 ft. scribed ¼ S9 S BT.

Fd. Ok by H. Johnstone, 8/1982 M90-26
Fd. Ok by K. Hoffine, 5/1994 M120-24