

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7416)

Set a stone 12x10x10", 8" in the ground for cor. of secs. 27, 28, 33, & 34 mkd with 1 notch on S & 3 notches on E edges, from which

- A fir, 48" dia., bears N.74½°E., 28½ lks., mkd: T30S R9W S27 BT.
- A cedar, 10" dia., bears S.8¾°E., 42½ lks., mkd: T30S R9W S34 BT.
- A cedar, 30" dia., bears S.55½°W., 57½ lks., mkd: T30S R9W S33 BT.
- A cedar, 30" dia., bears N.25°W., 99 lks., mkd: T30S R9W S28 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - Oct. 1965 - C.S. File 53/53-8

Found - 48", now 52" Fir N.74½°E., 28½ lks., good scar on tree.
10", now 20" Cedar S.9°E. 42½ lks., good scar on tree.
30", now 35" Cedar S.55½°W. 57½ lks., good scar on tree.
30" Cedar Stump N.25°W. 99 lks., opened for BT scribe.
12x10x10 Stone at corner 1 notch on S -3 notches on E
Set brass cap at Cor. mkd: County Surveyors T30SR9W S 28 | S 27
Office, 1965 S 33 | S 34
New BT - 14" Cedar bears N.79°W. 17.8 ft. scribed T30S R9W S28 CS BT.

Fd. Ok 4/1995, by K. Hoffine, M 119-59