TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7394

Set ¼ sec. post, from which
A live Oak, 12" dia., bears S.45°W., 11 lks.
A cedar, 36" dia., bears N.70°E. 29 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones - Joe Brady - Oct. 1965 - C.S. File 53/53-13

Found - 36" cedar now 60" N.70°E., 29 lks., open & find scribing "4"
12" Live Oak S.45°W., 11 lks. no trace of this tree.
Set brass cap at ¼ cor. mkd: COUNTY SURVEYORS OFFICE 1965
T30S R9W ¼ S16|S15
New BTs- 60" cedar N.70°E., 22.2 ft. scribed ¼ S15 CS BT.
26" Live Oak N.19°W., 43.4 ft. scribed ¼ S16 CS BT.

Ken Hoffine - For: Lone Rock Timber Co. - 10/2001 - M138-79

Found - Coos County brass cap 1.2 ft. above ground.
60" broken down Cedar snag bears N.70°E., 22.2 ft. (rec. N.70°E. 19.14 ft) chopped out face visible scribing & BT tag.
Stump remains of 26" Live Oak bears N.19°W., 43.4 ft. as per rec.
No trace of 12" Live Oak S.45°W., 7.3 ft.
16" D.Fir bears S.15°E., 24.3 ft. I tag tree.
Corner lies on 40% south slope in extremely heavy brush & scattered young D.Fir timber.

Carl Sweeden - For: Roseburg Resources Co - 11/2007 - M154-67

Found - BC up 1.3' above ground.
60" Cedar BT stump, N.70°E. 20.0' (19.14') snag down
Charred Oak BT stump, N.19°W. 43.4' per rec. not fd.
20" Live Oak BT, S.45°W., 7.3' not fd.
20" D.Fir BT, S.7°W., (S.15°E.) 24.3', scar vis. high up, Lone Rock tag.
New - 18" W.Fir BT, S.53°W. 33.2' scribed "E ¼ S16 BT" tag
Large boulder w/a 2 inch "+" chiseled on south face. Boulder measures 5'x2' protruding from ground, bears N.7°W., 38.4'