

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GL0 survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7396</p> <p>-----</p> <p>Set ¼ sec. post from which A fir, 40" dia., bears S.65°E. 19 lks. A fir, 20" dia., bears S.53°W. 32 lks.</p>
<p>Howard W. Johnstone - For: Roseburg Lumber Co. - Aug. 1982 - M90-26</p> <p>-----</p> <p>Found - 46" fir stump, S.65°E., 14.2 ft. (Rec. 12.5 ft.) Old axe marks. 27" fir stub, S.53°W., 21.9 ft. (21.1 ft.) Old cruiser mark</p> <p>Record distances fit to face of Orig. diameter. Corner fits creek call and ridge call to the south. Set - 5/8"x36" Iron rod and aluminum cap marked "LS 498". New BTs- 6" fir, East 65.8 ft. 15" cedar, N.37°W., 62.0 ft.</p>
<p>Brent Knapp - Crew: N. Fromdahl, J Ogden, & W. Keady - 7/25/2023 - C.S. File 65/113-7</p> <p>-----</p> <p>Found - LS 498 alum cap, mkd: T30S R9W 1982, ¼ 9 10, LS 498 21" Fir, East 65.8'; healed scar 46" stump, S.65°E. 14.2', new fir grown out of stump</p> <p>New - 15" Fir grown out of old bearing stump, S.58°E., 13.1', scribed "¼ S10 BT" "X" scribed on top edge of 5'x8'3' sandstone, S.11°E., 5.14'</p> <p>Note - 14" Fir, N.37°W., 4.0', scribed "¼ S9 BT" Compass decl. 15°E.</p>
<p> </p>