

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34, T29-9

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7374)

-----  
Set post cor. secs. 3, 4, 33 and 34, from which  
A Hemlock 15" dia., bears N.82°W., 16 lks. dist.  
A Hemlock 10" dia., bears S.37°W., 34 lks. dist.  
A Fir 24" dia., bears N.70°E., 33 lks. dist.  
A Chinquapin 20" dia., bears S.22°E., 31 lks. dist.

GLO resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6632-33)

-----  
Intersect at point for cor. of secs. 3, 4, 33 and 34. Post badly decayed and three witness trees destroyed. Set a Cedar post 3 ft. long, 4" sq., 24" in the ground, marked T29S S34 on NE.; T30S S3 on SE.; R9W S4 on SW.; and S33 on NW. faces, with 3 notches each on E. and W. edges in place of old cor., from which  
A Fir 30" dia., (old BT) bears N.70°E., 33 lks. mkd. T29S R9W S34 BT.  
A Fir 30" dia., bears S.45°E., 53 lks. dist. mkd. T30S R9W S3 BT.  
A Fir 6" dia., bears S.80°W., (lks. omitted), mkd. T30S R9W S4 BT.  
A Hemlock 8" dia., bears N.45°W., 29 lks. dist. mkd. T29S R9W S33 BT.

Ben B. Irving - Wit: LaVern Sutherlin; Herman Aydelot; T.L. Clinton - June 1927 - C.S. File 37/115

-----  
Identify by old Cedar post scribe marks rotted off. Four O.B.T.s Fir and stump of old Chinquapin check bearing and distance. Hemlocks check neither S. W. 41 lks. and N.55°W., 34 lks.

Searched for, not found - Oct. 1967 - DCSO

BLM resurvey by Wayne L. Rogers Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group #1579 - Surveyed Feb./April 1991 - (DCSO records Vol. 50 Page(s) 19235-36)

-----  
The sec. cor., determined at record bearing and distance from the remains of an original bearing tree;  
(Cont. Next Page)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir stump 30" dia., bears N.70°E., 33 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

T 29 S R 9 W  

S33	S34
S 4	S 3

T 30 S R 9 W  
 1991

from which new bearing trees;

A Fir 14" dia., bears N.70°E., 49 lks mkd. T29S R9W S34 BT

A Fir 7" dia., bears S.8°E., 27 lks. mkd. T30S R9W S3 BT

A Fir 9" dia., bears S.41°W., 23 lks. mkd. T30S R9W S4 BT

A Fir 7" dia., bears N.82°W., 15 lks. mkd. T29S R9W S33 BT

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point established by persons unknown, bears S.58°54'30"W., 0.305 chs. dist., monumented with an iron rod, 5/8" dia., firmly set, projecting 3" above ground.

From this same point, United States Coast and Geodetic Survey triangulation station "CAMAS 2", bears N.66°27'28"W., 74.658 chs. dist. (mean bearing and sea level distance), monumented with a brass tablet 3 1/2" dia., set flush in a concrete post, 12 x 12 ins., firmly set, projecting 12" above ground in the center of the base of lookout tower, with brass cap mkd. U.S.C. & G.S. CAMAS 1942.

Ken Hoffine - For: Lone Rock Timber Co. - Feb. 1995 (DCSO Rec'd & filed January 2015) - M168-78

(At the time of the survey) Unapproved 1992 BLM BCIP

Found - BLM brass cap in good condition.

17" D.Fir bears N.70°E., 32.1 ft (record N.70°E., 28.30 ft) scribing visible and BLM tag

32" orig. D.Fir stump bears N.70°E., 21.8 ft. BT scribing visible and BLM tag

8" D.Fir bears S.6 1/2°E., 18.2 ft (record S.8°E. 17.82 ft) scribing visible and BLM tag

10" D.Fir bears S.42 3/4°W., 15.3 ft (record S.41°W., 15.18 ft) scribing visible and BLM tag

8 1/2" D.Fir bears N.80 1/2°W., 10.0 ft (record N.82°W., 9.9 ft) scribing visible and BLM tag.

5/8" iron rod of unknown origin bears S.50°49'W., 20.23 ft.

Corner lies on flat ridge at corner of road. The corner is 25 ft East of road and 15 ft South of road. Road is a dirt road that leads to radio tower.

continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

49 U.S.G.S. CAMAS 1942 fd. BC in concrete block under signal  
Tree lookout tower bears: N.66°26'40"E., 4928.47 (1991 BLM  
resurvey Rec. N.66°27'28"E., 4927.43)

Coos County Surveyors Office - Michael Dado, Surveyor - Crew:  
Matthew Martin & Bill Hales - 2/5/2015 - C.S. File 65/87-49

-----  
Found - Old monument gone  
3 BTs, a 5/8" iron rod and a 1.5' dia., hole in the  
ground. We find the magnet set by Rogers in said  
hole.  
(1907) 24" D.Fir stump, N.71°30'E., 20.17' to face  
of stump, 9" out from center We find visible  
scribes, though the front 1/2 of the stump is  
gone. **We paint** the face in blue. Poor condition.  
A bent 5/8" iron rod S.61°30'W., 20.17' to a point  
where rod enters ground. Though bent to the  
South, the rod is in good condition and solid in  
the ground. (FD. 1991, origin unknown)  
(1991) 13" D.Fir tall stump, 6' tall, N.77°W., 9.89'  
to right side center. We find a healed blaze. **We  
add a new tag and paint** the face and a band  
around the stump in blue. Good condition.  
(1991) 14" D.Fir, S.45°W., 15.08' to left side  
center. We find a healed blaze and a BLM tag in  
place. **We paint** the face and a band around the  
tree in blue. Good condition.  
(1991) 13" D.Fir, S.5°E. 17.88' to left side center.  
We find a healed blaze and a BLM tag n place. **We  
paint** the face and a band around the tree in  
blue. Good condition.  
(1995) 24" D.Fir stump, N.71°E., 32.17' to heart  
center. We chop out face and find visible  
scribed, but no tag. **We paint** the top of the  
stump in blue. Poor condition.  
New - 15" D.Fir stump, 1' tall, N.22°30'E., 36.97' to  
spike and Coos Co. washer driven in at heart  
center. We chop an "X" in the face. We paint the  
"X" in blue and attach a yellow Coos Co. tag.  
We returned Rogers' magnet into said home and based  
on the existing accessories, we set a 2"x36"  
galvanized iron pipe with a 2½" brass cap  
(properly mkd), cemented into the top of the  
pipe, solid and flush in the ground, from which  
we measure the accessories (listed above)

Dec 17°

continued next page

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Joseph J Johnson, Cadastral Surveyor under Group #2864, surveyed Feb. 2017/Oct. 2018 - (DCSO Records Vol. 59 Page(s) 23689-2690)

-----

The cor. of secs. 3, 4, 33, & 34, on the S. bdy. of the Tp., perpetuated by Dado, on Feb. 5 2015, monumented with an iron post, 2½" dia. , firmly set, with top flush with the surface of the ground, with a brass cap mkd.

COOS COUNTY SURVEYOR  
T 29 S R9W  
S 33 | S 34  
S 4 | S 3  
T30S R9W  
2015

from which the remains of an original bearing tree  
A decayed fir stump, 24" dia., bears N.70°E., 21.8 ft., with scribe mark T visible on open blaze.

and the remains of the BTs mkd. by Rogers & Browning in 1991  
A decayed fir stump, 24" dia., bears N.70°E., 32.3 ft. with illegible scribe marks visible on open blaze.

A fir, 13" dia., bears S.8°E., 17.8 ft., with a healed blaze and an aluminum nail driven at the base on right side center.

A fir, 13" dia., bears S.43¾°W., 15.2 ft., with a healed blaze. (Record, S.41°W.)

A decayed fir stump, 13" dia., 6 ft. high, bears N.82°W., 9.9 ft., with a healed blaze.

and an accessory mkd. by Dado

A spike bears N.20¾°E., 36.9 ft., with washer mkd. COOS COUNTY SURVEYOR driven in the top of a fir stump 17" dia. with an X chopped in bark at the base.

and new accessories

An iron rod, 30" long, 5/8" dia., set 27" in the ground for a reference monument bears N.82°12'00"E., 32.81 ft., with aluminum cap mkd. RM T29S R9W S34 32.8 FT TO COR 2017 and an arrow pointing to the cor

A fir, 11" dia., bears N.62½°W., 91.3 ft., mkd. T29S R9W S33 BT.

From this cor., a point established by persons unknown, reported by Rogers and Browning in 1991, and was not utilized in the course of this survey, bears S.59°40'30" W. 20 27 ft., (Record, S.58°54'30"W., 20.1 ft.) monumented with an iron rod 5/8" dia., firmly set, bent to the SE with top flush with the surface of the ground.

**ON THE COUNTY LINE - CHECK WITH COOS COUNTY FOR POSSIBLY MORE INFORMATION**