

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7382)

Set ¼ sec. post, from which
An Alder 12" dia., bears S.20°E., 30 lks. dist.
A Fir 12" dia., bears N.10°W., 16 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7403)

This ¼ sec.cor.is burned. I find one witness tree. At cor. point, I set a stone 14x12x6 ins., 10" in the ground for ¼ sec. cor., mkd.¼ on N. face, from which
A Fir 12" dia., bears N.10°W., 16 lks. dist. mkd. ¼ S BT.
This is the original witness tree and it is dead. I therefore mark two new witness trees:
A Fir 17" dia., bears N.44½°W., 11½ lks. dist. mkd. ¼ S BT
A Fir 30" dia., bears S.72°E., 27 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 11, 1970 - C.S. File 53/53-60

Found - No trace of stone at ¼ corner.
30" now 50" D.Fir S.72°E., 17.8 ft., opened for scribe "1" "S"
17" now 28" D.Fir N.44½°W., 7.6 ft., opened for scribe, found burnt face, parts of scribe and old axe work.

Good call and distance to creek 72.0 ft. E., hits pretty good. Old camp nearby, probably fire place.

Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R9W ¼ S 34
T 31 S S 3

1970

New BT - 26" W.Fir N.9½°W., 34.2 ft. mkd. "¼ S34 CS BT"