

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7394

Set ¼ sec. post, from which
 A hemlock, 15" dia., bears N.12°W., 6 lks.
 A fir, 12" dia., bears S.70°W., 38 lks.

Donald Bentz - For: Roseburg Lumber - April 1980 - M82-79

Set - 5/8" iron rod with alum. cap
 18" Cedar bears N.70°W., 23.0 ft. scribed "¼ S15 BT"
 8" D.Fir bears S.80°E., 9.2 ft. scribed "¼ S15 BT"

Fd. Ok by K. Hoffine, 10/2001 - M138-79

Carl Sweeden - For: Roseburg Resources Co - 11/2007 - M154-67

Found - Alum cap up 0.3' above ground
 20" Cedar BT stump, N.70°W., 23.0' vis. scribe & tag, 6' tall.
 14" D.Fir BT stump, S.80°E., 9.2', scar & tag, 5' tall.
New - 2½" alum cap up 0.2' above ground, S.74°W., (magnetic) S.68°29'58"W., 27.65' per tie.
 2½" alum cap up 0.2' above ground, S.7°W., (magnetic) S.3°22'49"W., 25.09' per tie.
Both RMs stamped: ROSEBURG RESOURCES COMPANY
 REF MON
 2007
 T30S R9W
 1 SEC 15
 SEC 22 4
 LS 2752
Each rod & cap is marked with a painted metal post w/tag.
Magnetic declination 19.5° East.