TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7411)

Set a stone 16x14x12", 11" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 14" dia., bears S.33½°E., 39½ lks., mkd: ¼ S BT.
A fir, 14" dia., bears N.76¼°W., 45¼ lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - Oct. 1964 - C.S. File 53/53-25

Found - Rock 12"x14"x16" mkd: "¼" on W. face, in place.
14", now 24" D. Fir Snag S.33½°E. 26.1 ft. Open & find "¼" scribe. No trace of other BT.
Set Brass Cap at Cor. mkd: County Surveyors Office, 1964
T30S R9W ¼ S34|S35
New BTs- 8" D.Fir N.43°E. 8.5 ft. mkd: ¼ S35 CS BT.
6" W.Fir N.25°W. 8.8 ft. mkd: ¼ S34 CS BT.
Note - This corner lies approx. 60.0 ft N. of small creek on Steep, SW slope.