

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7411)

Set a stone 15x10x10", 10" in the ground for cor. of secs. 26, 27, 34, & 35 mkd with 1 notch on S & 2 notches on E edges, from which

- A fir, 7" dia., bears N.50°E., 20½ lks., mkd: T30S R8W S26 BT.
- A fir, 6" dia., bears S.26¾°E., 7¾ lks., mkd: T30S R8W S35 BT.
- A fir, 6" dia., bears S.40½°W., 64 lks., mkd: T30S R8W S34 BT.
- A fir, 6" dia., bears N.34½°W., 58¾ lks., mkd: T30S R8W S27 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby & Jack Barnett - Oct. 1964 - C.S. File 53/53-26

Found - Rock 15"x9"x8", set in ground with 2 notches on E. and 1 notch on S. edges. All 4 BTs alive and standing.

- 7" now 24" Fir N.50°E. 13.5 ft. Open & find axe face
- 6" now 30" Fir S.13¼°E. 5.1 ft., recorded as S.26¾°E.
- 6" now 30" Fir N.34½°W. 38.4 ft., shows scar.
- 6" now 30" Fir S.40½°W. 42.2 ft., shows scar.

Set Brass Cap at Cor mkd: County Surveyors T30S R9W S27|S26
Office, 1964 S34|S35

- New BTs-
- 26" D.Fir N.58°E. 30.2 ft. mkd: T30S R9W S26 CS BT.
 - 30" D.Fir S.13¼°E. 5.1 ft. mkd: T30S R9W S35 CS BT.
 - 16" D.Fir S.74°W. 36.4 ft. mkd: T30S R9W S34 CS BT.
 - 15" D.Fir N.32°W. 15.4 ft. mkd: T30S R9W S27 CS BT.