

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7414)

Set a stone 18x16x12", 13" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 8" dia., bears N.48½°E., 57 lks., mkd: ¼ S BT.

A fir, 10" dia., bears N.71½°W., 94½ lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - Oct. 1965 - C.S. File 53/53-10

Found - Stone marked "¼" on West Face for Corner.
10", now 29" Fir N.71½°W. 94½ lks., fd scribing "S"
8" Fir N.48½°E. 57 lks. (no trace of tree, fell in fire trail.)

Set Brass Cap at Cor. Mkd: County Surveyors Office, 1965
T30S R9W ¼ S27|S26

New BTs- 11" D.Fir bears S.37½°E. 15.0 ft. mkd: ¼ S26 CS BT.

13" D.Fir bears S.10°W. 11.0 ft mkd: ¼ S27 CS BT.

Note - This corner is about 80 ft. from the ridge top on the South Slope.

FD. Ok by D. Edwards 2/2007 M152-35