

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

| |
|--|
| <p>GL0 survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7392</p> <p>-----</p> <p>Set ¼ sec., post, from which A Fir, 36" dia., bears N.42°E., 109 lks. A Laurel, 6" dia., bears N.18°W., 22 lks.</p> |
| <p>Howard W. Johnstone - For: Roseburg Lumber Co. - Jan. 4, 1961 - C.S. File 51/163-4</p> <p>-----</p> <p>Found - 36" fir stump with scribing N.42°E., 72.0 ft. Set - 1"x30" Iron pipe 6" W.Fir S.8°E., 13.4 ft. 14" D.Fir N.15½°W., 86.5 ft.</p> |
| <p>Howard W. Johnstone - For: Roseburg Lumber Co. - Aug. 1982 - M90-26</p> <p>-----</p> <p>Found - 1" iron pipe, 1961 50" fir stump, N.42°E., 71.9 ft. scribe visible. 11" fir S.10°E., 13.5 ft. healed. 21" fir N.15½°W., 86.5 ft. healed. New BT - 11" fir N.49°W., 19.1 ft.</p> |
| <p>Mark Smalley - For: RFP - Bill Olson - Feb. 18, 2009 - C.S. File 65/66-12</p> <p>-----</p> <p>Found - 1" IP 14" Fir S.10°E., 13.5 good - healed. 29" Fir N.15½°W., 86.5 good - healed - tree will be cut to make room for a road. 17" Fir N.49°W., 19.1 good -healed. New BTs- 14" D.Fir N.81°E., 21.7 scribed "¼ S BT" 18" D.Fir S.4°W., 24.6 scribed "¼ S BT" Comp. decl. 14°</p> |
| <p> </p> |