TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Bushey, Deputy Surveyor, contract 613, dated April 29, 1893 - (DCSO records Vol. 17 Page(s) 7413)

---

Set a fir post, 4 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which
A fir, 28" dia., bears N.13¼°W., 39 lks., mkd: ¼ S BT.
A fir, 20" dia., bears S.84°W., 170 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby - Jack Barnett - Oct. 1964 - C.S. File 53/53-50

---

Found - Orig. 28", now 38" Fir N.13¼°W. 25.7 ft., showed scar, we open & find "/" scribe.
No trace of other BT.
Set Brass Cap at cor. mkd: County Surveyors Office, 1964 T30S R9W ¼ S26/S35
New BTs- 6" D.Fir S.29°E. 7.8 ft. mkd: ¼ S35 CS BT.
11" D.Fir N.28°E. l6.5 ft. mkd: ¼ S26 CS BT.

FD. OK BY D. EDWARDS 2/2007 M152-35