

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7390

Set ¼ sec. post, from which
 A fir, 18" dia., bears N.8°E. 16 lks.
 A fir, 15" dia., bears S.30°E. 29 lks.

DCSO 11/1965 C.S. File 53/53-15 - Reported as not found.

David Edwards - For: Plum Ck Timberlands- 2/2007 - M 152-35

BLM administrative surveys are of record for the south & west lines of sec. 26. From evidence on the ground it is clear that BLM also surveyed the North line. Boundary tags are found both East & West from the 3/4" IP at the north ¼ corner. Said pipe bears S.9°54'22"E., 2.274 from my computed mid-point. I accept the IP as the north ¼ corner because the position is within tolerances for the era in which it was set (probably 1981)
Found - 3/4" IP
 11" dia., Fir bears S.11°E., 10.38 ft.
 15" dia., hemlock bears N.44°W., 3.35 ft.
Set - 6 ft. steel posts 2 ft. west & 2 ft. east.