

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7391

Set ¼ sec. post, from which
 A fir, 30" dia., bears S.66°W. 12 lks.
 A chinquapin, 6" dia., bears N.60°W. 44 lks.

Howard W. Johnstone - For: Roseburg Lumber Co. - Sept. 15, 1961 - C.S. File 51/163-5

Found - 6" chinquapin N.60°W., 29.0 ft. (dead)
 38" D.Fir S.66°W., 7.9 ft. (now stump, scribe in good condition)
Set - 1"x30" iron pipe.
 17" D.Fir N.10°E., 93.5 ft.

Greg Lang - 7/5/2000 - C.S. File 65/30-18

Found - 1"x30" IP set by Johnstone (1961)
 existing BTs fd. per 1961 rec. are as follows:
 D.Fir stump S.66°W., 7.9 ft.
 17" D.Fir N.10°E., 93.5 ft. (now 21")
New - 11½" Hemlock bears S.66°E., 27.65' from IP - scribed "¼ S23 BT"
 12½" D.Fir bears S.55½°W., 70.55' from IP - scribed "¼ S23 BT"
 14" D.Fir bears N.69°W., 39.0' from IP - scribed "¼ S14 BT"
 21" D.Fir bears N.10¼°E., 92.6' from IP - scribed "¼ S14 BT" {measurement to previous accessory)
Note - Spikes were set in the side & bottom of BTs for dist. reference.
 Corner lies 763' west of ridge top & 50'± westerly of where a bench drops off toward a small creek to the West.

Fd. Ok by G. Smither, 10/2006 - M151-57

Fd. As per rec by D. Edwards - 2/2020 - M176-49 set 6' steel post 2' west.

1