TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 57 dated April 12, 1855 - (DCSO Records Vol. 17 Page(s) 7392

---

Set ¼ sec. post, from which
A cedar, 10" dia., bears S.58°E. 120 lks.
A fir, 20" dia., bears N.24°E. 55 lks.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M Godfrey & S. Bilow - July 18, 1958 - C.S. File 49/100-8

---

Found - Fir stump, now 44" dia., N.24°E., 36.3 ft. showing good BT scar.
I.Cedar, now 30" dia., S.58°E., 77.2 ft. (instead of 79.2 ft.) Chopped out lower blaze & fd good scribing "BT"
Set brass cap at corner mkd: ¼ S11 T30S R9W COUNTY SURVEYORS
S14 OFFICE 1958
Blaze & scribe New BTs -
20" D.Fir S.42°E., 18.7 ft. mkd: "¼ S14 CS BT"
6½" W.Fir N.17½°E., 13.7 ft. mkd: "¼ S11 CS BT"

Douglas Co. Surveyors Office - John M. Powell - Joe Brady - Oct. 1965 - C.S. File 53/53-2

---

Found - Brass cap at corner as shown in 1958 ren.
20" D.Fir, now 24" S.42°E. 18.7 ft., scribing visible.
6½" W.Fir, now Stump, N.l7½°E. 13.2 ft., scribe visible "BT".
New BT - 12" D.Fir N.83½°W. 36.1 ft. scribed "¼ S1l CS BT".

Gary Smither - For: Moore Mill & Lmbr Co. & Rsbg Resources Co - 10/2006 - M151-57

---

Found - 1958 county brass cap. 1965 and M71-5
BTs - 24" D.Fir stump S.44°E., 18.7 ft. with healed face & alum. tag.
17" D.Fir N.82°W., 35.7 ft W/healed face & alum tag
New BTs- 19" D.Fir S.33°E., 32.0 ft. to spike side center & alum. tag, scribe T30R9 ¼ S14BT
8" D.Fir N.13°E., 9.4 ft. to spike side center & alum tag, scribe T30R9 ¼S14BT
8 D.Fir N.10°W., 7.8 ft. to spike side center & alum. tag. scribe T30R9 ¼S14BT

Fd. Ok by D. Edwards, 2/2008 - C.S. File 65/64-2